



BNL-104088-2014-TECH

AGS.SN212;BNL-104088-2014-IR

Using the Linac Beam to Survey HEBT Quadrupole Magnets, Linac Position Monitors and SEM Units

R. K. Reece

July 1986

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No. DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

AGS Studies ReportDate(s) 11 July 1986 Time(s) 0001 - 0500Experimenter(s) R.K. ReeceReported by R.K. ReeceSubject Using the Linac Beam to Survey HEBT Quadrupole
Magnets, Linac Position Monitors and SEM Units.Observations and Conclusion

Since the redesign and conversion of the 200 MeV High Energy Beam Transport (HEBT) line from H^+ to H^- in 1981 there has been an uncertainty of the relative alignments of the quadrupole magnets, linac position monitors (LPM) and SEM units. Originally, the injection studies group had proposed possibly bleeding up the beam line to atmosphere and requesting an internal survey of the SEM units and correlating this with the quadrupole survey. This would however still leave the LPM's unsurveyed and require an extensive commitment of the survey and vacuum groups during the summer shutdown. An alternative procedure¹ was developed that would be performed using the beam and could be accomplished within 8-12 hours without breaking vacuum.

In two places in HEBT there are two sets of horizontal and vertical LPM's located between two quadrupoles (or a quadrupole and major horizontal dipole).

1. NX,Y31 and NX,Y35 are located between NQ29 and NQ42.
2. NX,Y221 and NX,Y246 are located between NQ218 and ND249.

The beam was first centered in both planes on the four LPM's indicated using a pair of horizontal and vertical dipoles between two upstream quadrupoles (ND9, ND16, NP9, NP16). The remaining steering elements from that point forward to ND249 were at zero current. Once the beam was centered in the four LPM's, upstream quadrupoles were varied by $\pm 10-20\%$ while monitoring any movement on the LPM's. Most of the quadrupoles were adjusted during this procedure and with an oscilloscope display amplitude of 100 mV/division, essentially no movement could be seen, (baseline sensitivity of $\pm 5-10$ mV was the accepted limit of the error in the measurement). This therefore implies that the quadrupoles and position monitors between tank #9 and ND249 have a common axis.

The calibration of the linac position monitor is as follows;

$$\frac{[\text{measured voltage (mV)}]}{[1.56 \text{ mV/mm}\cdot\text{mA}]} \frac{[\text{beam current (mA)}]}{[\text{beam current (mA)}]} \quad \begin{array}{l} \text{measured voltage limit} = 10 \text{ mV} \\ \text{beam current} = 30 \text{ mA} \end{array}$$

therefore, the possible error is 0.2 mm.

Previous measurements by Witkover indicate the LPM's in the HEBT/AGS matching section may not be properly calibrated. This area will be investigated in the fall.

An attempt was made to then determine if the linac HEBT SEM's also indicated they were/were not on the same common axis. However, the data rate was quite slow due to the AGS rep rate (1.6 seconds) and tank #9 was being pulsed only on the AGS pulse. The SEM's each take one point per pulse with 160 points per plane for 320 points (pulses) per SEM (H and V). Two SEM units may be used simultaneously and there are five SEM's. This would require 25 minutes minimum per complete data set and at least four sets were considered required. Therefore, this part of the study will be addressed in the fall when the linac (and tank #9) can be pulsed at 5 Hz.

Note

As an aside; quite by accident I noticed that movement on the HEBT LPM's can be seen, with no loss of beam, by adjusting the LEBT dipoles and even the 90° magnet in the dome. This implies that not only the linac but also the column is no longer a limiting aperture with H⁻ beam. This study was not in detail however but the general statement, I believe, is qualitatively correct.

¹ R.L. Witkover, private communication.

² R.L. Witkover, private communication.