



BNL-104227-2014-TECH

AGS.SN355;BNL-104227-2014-IR

AGS Programmed B Field vs. Hall Probe and Gauss Clock Readbacks

J. W. Glenn

November 1997

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No. DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

AGS Complex Machine Studies (AGS Studies Report No. 355) AGS Programmed B Field vs. Hall Probe & Gauss Clock Readbacks
Study Period: Nov. 26, Dec. 27, 1996; Jan. 9, 1997
Participants: J.W. Glenn and Various Logs
Reported by: J.W. Glenn
Machine: AGS
Beam: Gold
Tools: Main Magnet Program, Gauss Clock and Sieman's Hall Probe
Aim: To confirm agreement of AGS Main Magnet command program with readback

Mourning Numbers, Clyde printouts, the RF Dipole Log, and Archived Mmagnet control setups were scanned for readbacks and "commands" for this fall's running. There is a few percent discrepancy between the two views of the field in the AGS.

Injection fields were obtained from "mourning #'s" Hall probe readings. Extraction fields were from an assumed 436.4 Gauss at injection plus slow Gauss clock up-down's divided by 5; a picture of flat top, with some down counts recorded, show the field within 1/4% from FT start to clock read time. At the rf dipole porch, field was recorded by the Hall probe plus the fast Gauss clock up-down's divided by 20.

All points were taken at zero Bdot at least 30 mSec. into the flat top; there are no Bdot effects in the data.

The Sieman's power supply servos on current. J Sandberg reports the current error is occasionally monitored and is always found to be less than 1/2%.


"Re-normalizing" the program fields [by 123] to the Gauss clock and Hall data does not make the data "fit". The error is not simple scaling of the Hall probe and/or Gauss clock.

Thus:

There exists a significant error in the B field of the AGS, either in command or readback -- or both.

Command [MMag] vs Readback [GaussC+Hall]

error: gc/MMag-1



■ raw data gc/MMag-1

◇ gc/(MMag*.9744+21.08)-1

B pgm	B gc+hall	rdbk-cmnd delta	"fitted MMag" delta
412	436.4	5.92%	3.28%
412	436.6	5.97%	3.32%
1080	1067.6	-1.15%	-0.55%
6865	6685.8	-2.61%	-0.37%
8879	8625.8	-2.85%	-0.55%
11680	11428.2	-2.16%	0.23%
11680	11427	-2.17%	0.21%