

Measure Aperture on 28.5 GeV/c Flattop

E. Gill

October 1973

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.AT(30-1)-16 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

AGS FEB Studies

10/6-7/73

Blumberg
NO. 42

E. Rubin

F. Gill

During the first part of the run the available aperture at ≈ 28.5 BeV/c was explored by shifting the radius of the bunched beam on a flat top starting at ≈ 630 msec. Without the E-10, H-10 bumps and at $\approx 2.5 \times 10^{12}$ the aperture at H-7 was -1.8 mm to $+5.5$ mm. With the FEB bumps on the H-7 aperture was $+2$ mm to $+5$ mm with a sharp almost total loss toward the inside and a gradual loss toward the outside (at $\approx 2.5 \times 10^{12}$). At 4.5×10^{12} the aperture was about the same except that some vertical blow-up occurred at $+4$ mm and without loss.

With the H & V quads powered to the normal SEB values the aperture with bumps on was $+2.7$ mm to $+5$ mm; at full intensity $+2.5$ mm and $+4.5$ mm. The radial position of the beam prior to the radius shift used to explore the aperture had a slight effect on the observed aperture.

Using the new PUE's at D-4 & D-18 ($\approx \lambda/2$ apart) and summing them one found that the inside aperture with the bumps on was -1.7 mm and outside 3.5 mm. Thus one can conclude that the inside limitation using the single electrode pair at D-7 was due to an interaction between the bumps and the radial control system.