



Brookhaven
National Laboratory

BNL-103973-2014-TECH

AGS.SN95;BNL-103973-2014-IR

Vertical Injection Matching Studies

E. Raka

September 1977

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.EY-76-C-02-0016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Date 9/9/77 Time 1200-1400 Experimenters E. Raka, J-L LeMaire

Subject Vertical Injection Matching Studies

OBSERVATIONS AND CONCLUSION

Objectives: To measure the vertical beam size on the spiraling beam for different vertical matching conditions.

Procedure: We use the J19 vertical target to remove 10% of the beam intensity as usually done. All the AGS and linac parameters are identical to what they were before starting studies, but the linac pulse is shorter -- linac current was ≈ 67 mA.

Results:

- 1) We measured a vertical beam size, on a 5-turn injected spiraling beam of 1.58". This gives a normalized vertical emittance of 12.6π mm·mrad.
- 2) Using the destructive measurement device, we get for the same 90% beam conditions, a normalized emittance of 7.4π . Thus, there is a dilution factor of 1.6 during injection process. So the beam undergoes either vertical coherent oscillation or closed orbit distortion, or vertical mismatching, or all of them.
- 3) Because the steering conditions in HEBT IV were quite satisfactory, we concentrated on vertical matching. Making use of the matching code HOPI, we were able to change the vertical emittance parameters without affecting the horizontal ones. We ended up with a beam intensity increased by 5%, but the vertical size measurement could not tell any smaller size within the accuracy of the method.

When we went back to full intensity, it was lower than before studies for unknown reasons. We decided to set the new quad settings and were able to achieve 5% more in the injected intensity than before starting studies.