

LESB Secondary Intensity vs. C.Target Material

J. W. Glenn

February 1974

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.AT(30-1)-16 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Tuesday 2-28-74

Blumberg
NO. 54

Glenn, Stew Smith

A series of targets were tried at the "C" slow beam target station. The secondary flux was measured in the LESP. The results indicate:

- 1) Iridium and Heavy metal targets produce about equal flux.
- 2) Copper target's flux is about half.
- 3) 0.2" dia x 3" long targets produce ~30% more flux than 0.1" dia x 2 1/2" targets with no loss in purity of ~~the~~ the K to γ ratio.
- 4) The heat sink mounted on the far side of the target from the LESP does not increase the γ contamination in the beam.