



**Brookhaven**  
National Laboratory

BNL-103955-2014-TECH

AGS.SN77;BNL-103955-2014-IR

## Beam matching in HEBT IV

E. Gill

December 1976

Collider Accelerator Department  
**Brookhaven National Laboratory**

**U.S. Department of Energy**

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.E(30-1)-16 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

## **DISCLAIMER**

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MCR

AGS STUDIES REPORT

NUMBER 77

Date 12/22/76 Time 1200-1300 Experimenters E. Gill/ J.-L. LeMaire

Subject Beam Matching in HEBT IV

OBSERVATIONS AND CONCLUSION

In order to perform matching between the linac and AGS, the first thing done was to steer the beam properly through the matching section called HEBT IV so that we can decouple the parameters involved, steering and focusing.

To achieve the steering we use dipoles ND321, ND319, ND343, the beam position monitors NT352, NT377 and the zero degree beam line stationary flag.

Despite the fact that  $9.6 \cdot 10^{12}$  protons were accelerated, the beam position on this flag was out of the theoretical center by at least 1". This means either that the flag was misplaced or the beam mis-steered or both. Changing the tune of each quadrupole from Q18 to Q23, separately, we observed the corresponding displacements of the beam center on the flag. The beam was thus mis-steered in this action. It was not possible to center the beam on the flag because of lack of instrumentation. To define the beam direction, we need two reliable position measurements. We conclude from this study that the following be done:

- Survey of stationary flag and flag realigned (completed after studies)
  - Reinstallation of SEM's NE390, NE455, NE417 is needed
  - Additional steering dipole downstream of BMV is also needed
- } partially completed