

Horizontal Beam Size Measurement at F20

J. Herrera

April 1974

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.AT(30-1)-16 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

POINT OUT TO JOHN H. OUR EXPERIENCE THAT H.E. BEAM SIZE IS STRONGLY DEPENDENT ON MACHINE CONDITIONS.

No. 59

Horizontal Beam Size Measurements (data of 4/1/74)

Measurements of horizontal beam size were made by intercepting 5% of the beam with horizontally flipped aluminum targets.

Conditions

- 1) Horizontal targets at F-20 (pAV)
- 2) Beam intensity 5.5 to 6×10^{14} p/p
- 3) Average ring vacuum $\sim 3 \times 10^{-7}$ Torr
- 4) These conditions very similar to those existing on 3/9/74 when V size was measured.

was any effect made to vary transmission tuning, phase shift, and radius shifts, to just minimum HE horizontal size?

Results

- 1) Initial measurements shown on accompanying graph.
- 2) ^{H.E.} Horizontal size at F20 ≈ 0.68 " (~ 1.7 cm at pAV $\Rightarrow 2.1$ cm at pmax)
- 3) L.E. horizontal size ≈ 2.2 " (~ 5.5 cm at pAV $\Rightarrow 6.8$ cm at pmax)
- 4) Overall damping ratio $\approx \frac{2.2}{0.68} = 3.2/1$.
- 5) H.E. beam is larger than measurement made previously (see 5/10/73 data, which was made at 4×10^{14} p/p)
- 6) L.E. beam is smaller than measurement made previously (see 5/10/73 data), 2.2 inches compared with 2.9 inches.

Jellerson
3/8/74

This is larger than we see at H10 flog, which is between β_{av} and β_{max} . We see $\sim \frac{1}{2}$ " with well-behaved AGS.

HORIZONTAL BEAM SIZE (95%)

TIME IN ACCELERATION CYCLE

SPINNING BEAM

HORIZONTAL SIZE (INCHES)

TIME AFTER T_0 (MILLISECONDS)

- 1) HORIZONTAL TARGET AT F_{20} (BAY)
- 2) BEAM INTENSITY: 5.5 TO 6.0×10^{12}
- 3) DATA OF 4/1/74

