



Brookhaven
National Laboratory

BNL-103939-2014-TECH

AGS.SN61;BNL-103939-2014-IR

Beam Tuning to Maximize Accelerated Beam

E. Raka

April 1974

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.AT(30-1)-16 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Low Field & Capture Studies (4/16/74), Raker, Gill, Herrera

The machine was "tuned" in order to maximize the accelerated beam.

Conditions

- 1) Lincac run very well after 0100, giving ~ 70 ma for 140 μ sec. Max after multistart $\sim 1.2 \times 10^{13}$ p/p.
- 2) Per J. Claus, lincac inductances were up by approximately 1.5 times their normal values.
- 3) Average ring vac $\sim 3 \times 10^{-7}$ Torr.

Results

- 1) The max beam accelerated was 7.22×10^{12} p/p, with 7.5×10^{12} on the early counter. The machine ran steadily in the 7×10^{12} region.
- 2) In order to achieve 1) it was necessary to compromise the early beam counter reading and the effective turns ratio.
- 3) At one point, we could get 9.45×10^{12} p/p on the early monitor with about 8 turns. However, horizontal coherence appeared at about 20 ms after injected and the beam was very erratic with maxima of about 6.8×10^{12} p/p. The v values under this condition were ($v_H = 8.84$; $v_V = 8.75$).

JGH, 4/19/74