



BNL-103942-2014-TECH

AGS.SN64;BNL-103942-2014-IR

Beam Capture in High Voltage (150 KV peak) mode. Horn instabil.

E. Raka

May 1974

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.AT(30-1)-16 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

5/10/74

AGS Studies 0200-0600 E. Raka

The first part of this period was used to adjust the RF parameters for the high voltage capture mode (≈ 150 Kv peak) giving a peak intensity of 5.5×10^{12} . Also the FEB was set up in parallel operation. At $\approx 2.5 \times 10^{12}$ the horizontal instability seen on 3/15 and earlier occasions was observed at around 500 msec (H-7 position $\pm 2-3$ mm and no debunching at transition). When the intensity was increased to $> 5 \times 10^{12}$ the horizontal growth occurred at ≈ 350 msec for H-7 position > 0 . For H-7, < 0 the first vertical growth was seen at about 320 msec. This is an individual bunch instability with a very rapid growth rate (e-folding time a few msec!) that results in beam loss. The intensity threshold was not established but it is $> 2.5 \times 10^{12}$.

The remainder of the time was spent studying the horizontal instability as a function of radial position. It would seem what m time as a function of r for a fixed intensity. Also ~~the~~ the nature of the signal changes on different electrodes as one changes r . As noticed previously one does not see the same type of difference signal on the individual electrodes (H-7 66-15 for example) for a given set of conditions. Thus the nature of this growth remains a mystery.