

BNL-103917-2014-TECH AGS.SN37;BNL-103917-2014-IR

Extract FEB up to 8 Bend Point

G. W. Bennett

September 1973

Collider Accelerator Department

Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.AT(30-1)-16 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

NO. 37

BENNETT, BLUMBERG, CASEY, CULWICK, GLASMANN, GUTHY, KEANE, RAKA SCHEDULED: 000/- 0800 ACTUAL: 000/- 0730

RADIATION SURVEY. FRACTIONAL EXTRACTIONS.

- I. STABILITY OF HID EJECTOR MAGNET POWER SUPPLY WAS

 STUDIED BY OBSERVING SHUNT SIGNAL ON TEKTRONIX 555
 WITH TYPE Z PLUG-IN. WE SAW ~ 4 % FLUCTUATIONS
 IN AMPLITUDE OF 21000 A PEAK CURRENT, WHICH COULD
 ACCOUNT FOR PREVIOUSLY OBSERVED ~ 1" FLUCTUATIONS IN
 BEAM POSITION ON UIS FLAG. HOWEVER, SCHIRNER POINTS
 OUT THAT SHUNT SIGNAL CAN FLUCTUATE FOR REASONS OTHER
 THAN CURRENT VARIATION, SO CAUSE OF POSITION VARIATION
 IS STILL UNGERTAIN.
- 2. BEAM SPOT WAS OBSERVED ON V273 FLAG (~ 8° BEND POINT), verteally trumcated. WE LATER DISCOVERED THAT TOP JAW OF U259 COLLIMATED WAS LEFT IN. WITH JAW REMOVED, SPOT WAS > 2" venticacy AND ~ &" HORIZ. CALEULATED VALUES FOR FRACTIONAL EXTRACTION AT THIS POINT ARE .3" H X I" V. WE DID NOT HAVE CALCULATED LENS SETTINGS, HOWEVER, SINCE INCREASING UQZ EXCITATION STEERED BEAM. WE HAD UPI AT ~60% (52 mv) STREWETH AND UPZ ~ 20% (17 mv). STEERING BY QUADS IS EXPECTED SINCE SPOT AT UIS FLAG IS ~ 1 LOW . THE STOT WAS HORIZONTAWY WELL CENTERED AT UZTS (~ 16"OFF) AND VERRY STABLE IN POSITION. THE 440 BOND WAS VARIED BY ~ ± 200 WITH HEGGISIBLE MOTION OF ULTS SPOT. THIS PROVES THAT WE HAVE MOHENTUM RECONBINATION AT 80 POINT, AS INTENDED. THEREASING EXCITATION OF QUADS UQ3,...7 FROM 1821 A TO BYOA Produced SPOT AT UNBS OF E"VX ~ L"H SO ITS PRETTY CLEAR THAT WE CAN GET THROUGH THE 234" 80 APERTURE.
- 3. RADIATION SURVEYS WERE TAKEN WITH ABOVE CONDITION AND WITH "FAULT" CONDITION OF UNSO JAW GLOSED. LEVELS ABOVE EARTH SHIELD WERE ~ 1.5 Rem/HR WITH FAULT AND "YXIO" P/P (25% of 1.7x10" CBM) EXTRACTION. WITH BETTER SET UP, LEVELS ABOVE EARTH SHIELD DROPPED TO ~500 MR/AR MY ~ 60 MR/M IN RECTIFIER BLDG, AND ~3.5 Remy ON SIDE OF EARTH SHIELD DOWNSTREAM OF 80. WITH A FACTOR OF 10 MORE INTENSITY, WE MAY BE IN TROUBLE IN LECTRICR BLDG. UNLESS UP AND UIZ COLLINATORS