

Effect of Interpulse Dwell and Peak Field History on Accelerated Beam Intensity

R. Allard

November 1984

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No. DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

AGS Studies ReportDate(s) Sunday, November 4, 1984 Time(s) 1100-1600Experimenter(s) R. Allard, K. Brown, J.W. GlennReported by K. BrownSubject(s) Effect of Inter-pulse Dwell and Peak Field History
on Accelerated Beam IntensityObservations and ConclusionsAbstract

The effect of the inter-pulse dwell on the accelerated beam intensity was measured and found not to be a critical parameter. By tuning the injection peaker, little change was seen in the beam intensity for any dwell time as far down as zero. No effect was seen in the beam intensity from the peak field history. It was found that zero dwell corresponds to 43 ms since the voltage in this interval does not rest at zero.


Method

Siemens was set up with a flattop which was varied to achieve different dwell times. The beam intensity (ICBM and 3CBM) was recorded with and without tuning the injection peaker (assuming that compensation for the remnant field is done by tuning the injection peaker). Then the beam intensity was recorded with varying the peak field with a constant dwell. Tuning the injection peaker was not necessary.


Distribution: Dept. Admin.
Operations Coordinators
Operators
L. Ahrens
E. Gill
J.W. Glenn
J. Grisoli
S. Naase
S. Wingard
MCR File

43 ms dwell (zero dwell), 20 ms/div.


From H20 backleg.




74 ms dwell, 20 ms/div.




146 ms dwell, 20 ms/div.




300 ms dwell, 50 ms/div.



Graph II - ICBM, 3CBM vs. Dwell w/ tuned peaker.





Graph III - ICBM, 3CBM vs. G. S. Cup

