

Extract Fraction of Beam at H10, Observe Affect on SEB

G. Bagley

May 1973

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.AT(30-1)-16 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Bagley, Bennett, Blumberg, Curtiss, Glasmann, Glenn, Guthy, Keane, Raka, Schirmer, Soukas

Scheduled: 1030-1230 Actual: 1030-1300

Objective: Extract a fraction f of the debunched, internal beam prior to the SEB spill and observe possible effect on SEB spill structure or efficiency. Fractions of interest are $.02 \leq f \leq .1$

Result: Various fractions of the circulating ($\sim 3.5 \cdot 10^{12}$ ppp) beam were extracted — up to 50% judging by the decrease in the SEB — for various currents in the C15, E15 Kickers. We were unable to measure directly the amount of beam extracted due to instrumentation problems. We observed approximately a 10% decrease in beam available for the G10 target + SEB spill when the E10 and H10 magnets were positioned and the E and H orbit bumps were energized, indicating the need for larger amplitude orbit deformations so that the extraction magnets can be positioned at larger radii. The first test of powering the H-superperiod backleg windings with two power supplies was made — one supply powering H2 + H3 and the other H16 + H17. The supplies worked well so we should have the capability of up to 1400 Amps in the backleg windings in the future rather than the 1000 A present limit.

The horizontal half-size of the debunched, high intensity internal beam appeared to be about 5mm larger than the bunched, $1.5 \cdot 10^{12}$, ppp beam, we previously worked with.

There was no obvious deterioration of SEB spill structure. All G10, B and C target users took data during this period; in particular, the Kycia group was asked to look for expected modulation at the 370 KHz rotation frequency. No effect in their "accidentals" was reported.