



BNL-105090-2014-TECH

Booster Technical Note No. 43;BNL-105090-2014-IR

Booster parameter list with 60 Kv RF voltage and increased ejection energies

Z. Parsa

June 1986

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

BOOSTER PARAMTER LIST WITH 60 KV RF VOLTAGE
AND
INCREASED EJECTION ENERGIES

Booster Technical Note
No. 43 A

Z. PARSA
JUNE 18, 1986

ACCELERATOR DEVELOPMENT DEPARTMENT
Brookhaven National Laboratory
Upton, N.Y. 11973

ABSTRACT

THIS NOTE DESCRIBES THE PARAMETER LIST FOR THE AGS - BOOSTER. THE FOLLOWING CHANGES WERE MADE AND SHOULD BE NOTED: THE RF VOLTAGE WAS RAISED TO 60 KV; RF CAVITIES FOR PROTON ACCELERATION WAS CHANGED FROM ONE TO TWO; THE EJECTION ENERGY FOR PROTON WAS INCREASED (FROM 1GEV) TO 1.5 GEV, AND FOR H.I. (GOLD, FROM .32) TO .35 MEV/AMU. ADDITIONALLY, THE LARGE Q5 QUADRUPOLES WERE REPLACED BY THE NORMAL-SIZED MAIN RING QUADRUPOLES.

INTRODUCTION

This note describes the parameter list of the AGS-Booster with the 60KV RF Voltage for protons and tunes of 4.82 and 4.83. The chromaticity correction sextupole configuration is 1,2,4,7 and the eddy current sextupole strengths are taken to be 0.12 Tesla per meter square [1]. The following changes were made and should be noted: The rf voltage was raised to 60 kV; rf cavities for proton acceleration was changed from one to two; the ejection energy for protons was increased (from 1 GeV) to 1.5 GeV, and for Heavy Ions (GOLD, FROM .32) TO .35 MEV/AMU. Additionally, the large Q5 quadrupoles were replaced by the normal-sized main ring quadrupoles. A schematic layout of the Booster lattice and its superperiods are also included [2-4]. In section II the present values of the Booster parameters are tabulated, [note that, the values listed are for theoretical calculations]. This updates the Booster parameter list given in Reference 5.

References:

1. Calculation of Eddy Currents, BST/TN 4, G. Morgan and S. Kahn, (January 1986).
2. Booster Lattice, Booster Tech. Note No. 1, E. Courant and Z. Parsa, (January 15, 1986).
3. Chromaticity Correction for the AGS - Booster with 1,2,4,7 Sextupole Configuration, BST/ TN 17, E. Courant and Z. Parsa, (March 5, 1986).
4. Booster Coordinates, Booster Tech. Note No. 6, Z. Parsa, (January 28, 1986).
5. AGS - Booster Parameter List, Booster Tech. Note No. 2, Z. Parsa, (January 16, 1986); BST/TN 20, Z. Parsa, (March 10, 1986); and BST/TN 25, Z. Parsa, (April, 1986).
6. Private communication, Y. Y. Lee.

AGS BOOSTER PARAMETER LIST

LATTICE

| | |
|--------------------|------------------------|
| CIRCUMFERENCE | 201.78 m (1/4 AGS) |
| PERIODICITY | 6 |
| NUMBER OF CELLS | 24 FODO |
| LENGTH | 8.4075 m |
| PHASE ADVANCE/CELL | 72.3 , 72.45 [degrees] |
| TUNES | QX= 4.82, QY= 4.83 |
| BETAX MAX/MIN | 13.865/3.5754 |
| BETAY MAX/MIN | 13.644/3.7033 |
| XP MAX | 2.9515 m |
| TRANSITION GAMMA | 4.8812 |

| ENERGY [MeV] | @ INJECTION | @ EJECTION |
|--------------|---------------------------------------|--|
| PROTONS | 200 MeV [BRHO=21.4962 kG-m] | 1.5 GeV [BRHO=75.069 kG-m] |
| HEAVY IONS | 1 > MeV/amu [*BRHO=1.4403A/Q kG-m] | P=5.252 Q/A GeV/amu-c [BRHO=175.194 kG-m] |

[Q is the charge of the Heavy Ions (whether fully stripped or not) delivered from the Tandem.]

* At 1 MeV/amu

RF SYSTEM

NUMBER OF STATIONS (4 IN TOTAL)

2 FOR PROTONS (INCLUDING POL PROTONS)

2 FOR HEAVY IONS

[where POL== POLARIZED]

HARMONIC NUMBER

3 FOR PROTONS (INCLUDING POL PROTONS)

3 FOR HEAVY IONS (1 FOR RHIC)

FREQUENCY RANGE (MHz)

FOR PROTONS (INCLUDING POL PROTONS) 2.5 - 4.12

FOR HEAVY IONS - (- FOR RHIC)

PEAK RF VOLTAGE [KV]

FOR PROTONS (INCLUDING POL PROTONS) 60

FOR HEAVY IONS 17

ACCELERATION TIME [M-SEC]

FOR PROTONS (INCLUDING POL PROTONS) 50

FOR HEAVY IONS 500

REPETITION RATE

FOR PROTONS 7.5 Hz (4 PULSES/AGS PULSE)
 FOR POL PROTONS 1 Hz (1 PULSE/AGS PULSE)
 FOR HEAVY IONS 1 Hz (1 PULSE/AGS PULSE)

DIPOLES

 [DIPOLES ARE CURVED AND WEDGED FOR 0 ENTRANCE ANGLE]

NUMBER 36
 LENGTH (MAGNETIC) 2.4 M
 GAP 82.55 MM
 GAP VACUUM CHAMBER 66 MM
 -4
 GOOD FIELD REGION (<10) 16 X 6.6 CM

INJECTION FIELD [KG]

 FOR PROTONS (INCLUDING POL PROTONS) 1.5633
 FOR HEAVY IONS 0.1047 A/Q

EJECTION FIELD [KG]

 FOR PROTONS (INCLUDING POL PROTONS) 5.459
 FOR HEAVY IONS 12.740

LAMINATION THICKNESS 1.5 MM
 [0.6 MM AROUND ENDS]

QUADRUPOLES

 NUMBER 48
 LENGTH (MAGNETIC) 0.50375 M
 APERTURE 16.52 CM

 VACUUM CHAMBER AP. HORIZ. VERT.
 [AP.== APERTURE] 15.25 CM 5 CM
 *
 WITH GF = 11.999 [KG/M]
 GD = -12.369 [KG/M]

[* SPECIAL QUADRUPOLE (Q5) FOR INJECTION.]

INJECTION POLE TIP FIELD [KG]

 FOR PROTONS (INCLUDING POL PROTONS)
 BF = 0.9899, BD = 1.0204
 FOR HEAVY IONS
 BF = 0.06635 A/Q , BD = 0.0683 A/Q

EJECTION POLE TIP FIELD [KG]

 FOR PROTONS (INCLUDING POL PROTONS)
 BF = 3.457 , BD = 3.5635

FOR HEAVY IONS
 BF = 8.0706 , BD = 8.3078 .

LAMINATION THICKNESS 0.6 MM

FIELD QUALITY
 SEXTUPOLE HARMONIC 0.0
 (6 THETA/2 THETA) (SHAPE POLE TIP TO ELIMINATE)
⁻⁴
 ALL OTHER HARMONICS < 10

SEXTUPOLES

 LOCATION 1,7 (SF), 2,4 (SD)
 NUMBER 24 (12 SF + 12 SD)
 LENGTH 10 CM
 APERTURE 16.52 CM

AT 1.5 GEV WITH INTEGRATED STRENGTH [T/M]:

INJECTION POLE TIP FIELD [KG]

 FOR PROTONS (INCLUDING POL PROTONS) 0.45761
 FOR HEAVY IONS 0.03065 A/Q

EJECTION POLE TIP FIELD [KG]

 FOR PROTONS (INCLUDING POL PROTONS)
 FOR HEAVY IONS

OTHER PARAMETERS

 MAX. VACUUM PRESSURE (N2 EQU.) 3×10^{-11} TORR

MAX. INTENSITY (PARTICLES PER PULSE)

 FOR PROTONS $1 - 3 \times 10^{13}$
 FOR POL PROTONS 10^{12}
 FOR HEAVY IONS $10^{11} \times 2$
 10 A/Q