

H- stripping in the Booster proton injector line

R. A. Thomas

May 1987

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy
USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

H⁻ STRIPPING IN THE BOOSTER PROTON INJECTION LINE

AD
Booster Technical Note
No. 79

RICHARD A. THOMAS

MAY 7, 1987

ACCELERATOR DEVELOPMENT DEPARTMENT
Brookhaven National Laboratory
Upton, N.Y. 11973

H⁻ Stripping in the Booster Proton Injection Line

Richard A. Thomas

A purely electric or magnetic field in one frame of reference will appear as a mixture of electric and magnetic fields in another frame of reference if the second coordinate system is in motion relative to the first. Therefore a particle moving at velocity v through a magnetic field of magnitude B will experience an electric field of magnitude E given by the Lorentz transformation¹

$$E = \gamma v B = c \beta \gamma B \quad (\text{MKS units})$$

For the H⁻ injection line this electric field might cause stripping of the H⁻ ion to neutral hydrogen. The decay of H⁻ ions in an electric field can be represented by the differential equation²

$$\frac{df(t)}{dt} = - \frac{f(t)}{\tau(t)}$$

where $f(t)$ is the fraction of the beam remaining at time t , $f(t=0) = 1$, and $\tau(t)$ is the average lifetime of an ion in the field E in which the ion is moving at the time t . If the magnetic field is constant along the path of the particle then τ is constant and $f(t)$ is simply an exponential decay function.

The average lifetime of H⁻ ions as a function of the electric field strength has been found experimentally³ to be

$$\tau(E) = \frac{7.96 \times 10^{-6} \text{ Vs/m}}{E} \exp \left[\frac{4.256 \times 10^9 \text{ V/m}}{E} \right]$$

The H⁻ transfer line to the Booster requires that the ions bend through an angle of 126.165° (excluding the 7.5° bend at the kicker in the HEBT line and the 6.968° bend in Booster dipole magnet MDC5 through which the beam is injected). For 200 MeV H⁻ ions, $\beta = v/c = 0.5662$ and $B\rho = 2.1496 \text{ T}\cdot\text{m}$. Therefore, since

$$BL = (B\rho) \theta$$

where θ is in radians, and BL is the product of the constant dipole field of the bending magnets in the H⁻ line and their total magnetic length,

$$BL = 1.1834 \text{ T}\cdot\text{m}$$

¹John David Jackson, **Classical Electrodynamics**, p. 380.

²K. Prelec, "Stripping of H⁻ in a Magnetic Field," AGS Division Technical Note No. 110, June 4, 1974.

³G. M. Stinson, *et. al.*, Nucl. Instrum. Methods, **74**, 333 (1964).

Physical restrictions and construction requirements suggest the use of four bending magnets of equal length, l , so $L = 4l$. We wish to choose a length that gives insignificant stripping.

$$\% \text{ stripped} = 100\% \left[1 - e^{-t/\tau} \right]$$

where $t = 4l/v$ and τ is calculated from the equations given above. The results are shown in the table below. Ramesh Gupta, who is specifying the design of the H^- injection line, has chosen the values of 1.3 m and 0.91 T for the lengths and strengths of the four dipole magnets since these values give negligible ion stripping.

l (m)	B (T)	τ (μ s)	t (ns)	% Lost (%)
0.5	2.367	1.01×10^{-4}	11.78	100.00
0.6	1.972	6.97×10^{-4}	14.14	100.00
0.7	1.691	4.66×10^{-3}	16.50	97.09
0.8	1.479	3.06×10^{-2}	18.85	46.04
0.9	1.315	1.97×10^{-1}	21.21	10.20
1.0	1.183	1.26	23.57	1.86
1.1	1.076	7.92	25.92	0.33
1.2	0.986	4.96×10^1	28.28	0.06
1.3	0.910	3.08×10^2	30.63	0.01
1.4	0.845	1.90×10^3	32.99	0.00
1.5	0.789	1.17×10^4	35.35	0.00
1.6	0.740	7.15×10^4	37.70	0.00
1.7	0.696	4.35×10^5	40.06	0.00
1.8	0.657	2.64×10^6	42.42	0.00
1.9	0.623	1.60×10^7	44.77	0.00
2.0	0.592	9.66×10^7	47.13	0.00