

AUTOMATIC TARGET TRANSFER SYSTEM

C. Christianson

July 1965

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.AT-30-2-GEN-16 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Accelerator Department
BROOKHAVEN NATIONAL LABORATORY
Associated Universities, Inc.
Upton, L.I., N.Y.

AGS DIVISION TECHNICAL NOTE

No. 3

C. Christianson
July 26, 1965

AUTOMATIC TARGET TRANSFER SYSTEM

1. The subject system has proved reliable mechanically with no malfunctions during approximately 3000 cycles.
2. Electrical malfunctions have been confined to switch contacts sticking. This appears to have been corrected. Also, switches with greater capacity have been ordered and will be installed and tested.
3. To date, these major changes have been found to be desirable:
 - a) place the programmer upstream from the airlock and near the tunnel floor. (This can be done with the present programmer)
 - b) Redesign the programmer envelope to permit plug-in modules where feasible, and allow easy access to all other components.
4. Shall change (b) be made before the system is installed at G-10 outside?
5. I request your guidance on which course of action will best suit the overall AGS operation.

distribution: A. van Steenberg
A. Maschke
J. Grisoli
C. Flatau
G.K. Green
J.P. Blewett
L.W. Smith
J. Spiro
E.W. Dexter
H. McChesney
I. Polk
M. Plotkin
L. Leipuner
J.R. Sanford
G. Wheeler