

BNL-104534-2014-TECH

AGS/AD/Tech Note No. 102;BNL-104534-2014-IR

BEAM INTENSITY IN THE AGS

A. van Steenbergen

January 1973

Collider Accelerator Department Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.AT(30-1)-16 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, worldwide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Accelerator Department BROOKHAVEN NATIONAL LABORATORY Associated Universities, Inc. Upton, New York

- 11 J

AGS DIVISION TECHNICAL NOTE

No. 102

A. van Steenbergen January 20, 1973

BEAM INTENSITY IN THE AGS

Since turn-on after the recent shutdown, sufficiently improved multiturn (horizontal only) stacking efficiencies have been observed^{*} that it seemed worthwhile to update and expand on Technical Note No. 90 (J.C. Herrera, "Beam Intensity in the AGS", January 20, 1972). However, in addition to stating here the "injection" and "capture" efficiency numbers, as defined in Technical Note 90, more relevant figures of merit for the transverse stacking and injection performance, i.e., the circulating beam current to linac current ratio, and the absolute value of circulating beam current immediately after multiturn injection completion, are given. This is listed in the following table, where the first two columns are a repeat from Tech. Note 90, expanded with $I_c(1)$ values and $[I_c(1)/I_L]$ ratios. The additional columns reflect more recent performance figures using "horizontal stacking only" injection.

"Due to inflector system improvements, better beam matching control, enlargement of the horizontal acceptance (10 to 15%) due to reduction of horizontal closed orbit errors and some reduction of the 200 MeV emittance associated with improved linac performance. [Note: Since $\eta(1)$ depends on t_L (see definitions in the table), which may or may not be set up to verlap the acceptance (time) aperture generously, and also, since the "per turn acceptance" varies strongly during the t_L duration, $\eta(1)$, as defined, is a poor criterion of injection tune-up and performance. As an example, the following numbers are cited, using recent observations:

$t_L^{(\mu sec)}$	I _L (mA)	N(1) (ppp)	N(2) (ppp)	୩(1)	[୩ (2)]	[Ŋ(1)Ŋ(2)]
56	35	8 10 ¹²	3.5 10 ¹²	62%	44%	27%
100	35	12 10 ¹²	4.0 10 ¹²	48%	33%	16%

These numbers were obtained with only a change in linac pulse length. No injection conditions or parameters were changed.

For this reason, in addition to using N(2) (measured immediately before transition) and N(1) or $I_c(1)$, immediately after stacking, the guiding figures of merit to indicate status of optimization of transverse stacking and longitudinal capture (and linac performance!) which are presently being used are $(I_c(1)/I_1)$ and $\eta(2)$.

- 2 -

	50 Mat	200 Mov	{		Peak N(2)			1
	Injection	1/18/72		3/25/72	Shutdown		10/22/72	1/10/73
I _L (mA)	40	40		38	54		40	41
t _L (µsec)	86	48		57	57		100	120
tyrns	10	10		12	12		21	. 25
pr/mA turn	<u>5 10¹⁰</u>	<u>3 10¹⁰</u>		3 10 ¹⁰	3 10 ¹⁰		3 10 ¹⁰	3 10 ¹⁰
NL	20 10 ^{1 2}	12 10 ^{1 2}		13.7 10 ¹²	19.0 10 ¹	3	25 10 ¹²	30 10 ¹²
N(1)	10 1012	7.2 10 ¹²		7.0 lợi 2	9.6 10 ¹	3	14 10 ¹²	12.8 10 ¹²
N(2)	3 10 ¹²	2.6 10 ¹²		4.5 10 ¹²	<u>5.8 10¹</u>	3	<u>4 1012</u>	<u>7 1012</u>
$N(1)/N_{L} = \eta(1)$	50%	60%	•	51%	50% <u> </u>		56%	42%
N(2)/N(1)≠7)(2)	30%	36%	•	64%	60%		28%	54%
Ŋ(1)Ŋ(2)	15%	22%		33%	30%		16%	23%
I _c (1)(mA)	336	242		235	322		<u>470</u>	430
$(I_c(1)/I_L)$) 5.0*	6.0		6.2	6.0		<u>11.7</u>	10.5
· · · · · · · · · · · · · · · · · · ·								



*Corrected for (β_{50}/β_{200}) ratio.

time (1) , tranverse capture complete
" (2) , total capture process complete

55 \$ L