

Booster Parameter List

Z. Parsa

January 1986

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

BOOSTER PARAMETER LIST

*Booster Technical Note
No. 2*

*Z. Parsa
January 16, 1986*

*HIGH ENERGY FACILITIES
Brookhaven National Laboratory
Upton, N.Y. 11973*

ABSTRACT

THIS NOTE DESCRIBES THE PARAMETER LIST FOR THE AGS - BOOSTER. A SCHEMATIC LAYOUT OF THE LATTICE AND ITS SUPERPERIODS ARE ALSO INCLUDED.

INTRODUCTION

In this note we describe the parameter list of the AGS - Booster. In section II the present values of the Booster parameters are tabulated. This updates the Booster parameter list given in References 1 and 2. Schematic diagram of the lattice [3,4] showing the layout of the AGS Booster, the labling convention of the lattice and its superperiods are also included.

References:

1. AGS Booster Conceptual Design Report, Vol.I, (April 1984);
AGS Booster Parameter List, Y.Y. Lee, (Sept. 26, 1985).
2. R & D For The AGS Booster, E.B. Forsyth, (Dec. 12, 1985).
3. Booster Lattice, Booster Tech. Note No. 1, E. Courant and Z. Parsa, (January 15, 1986).
4. Booster Coordinates, Booster Tech. Note No. 3, Z. Parsa, G.F. Dell (January 1986).

AGS BOOSTER PARAMETER LIST

ENERGY [MeV]

INJECTION:

PROTONS	200 MeV
POL PROTONS	200 MeV
HEAVY IONS	> 1 MeV/AMU

[POL == POLARIZED]

EJECTION (MAXIMUM)

PROTONS	1	GeV
POL PROTONS	1	GeV
HEAVY IONS	P = 5	Q/A GeV/AMU

[Q is the charge of the Heavy Ions (whether fully stripped or not) delivered from the Tandem.]

LATTICE

CIRCUMFERENCE	201.78 M (1/4 AGS)
PERIODICITY	6
NUMBER OF CELLS	24 FODO [SEPARATE FUNCTION, MISSING DIPOLES]
LENGTH	8.4075 M
PHASE ADVANCE/CELL	71.25
QX ~ QY	4.75
BETAX MAX/MIN	13.88/3.67 M
BETAY MAX/MIN	13.67/3.80 M

XP MAX	2.94 M
TRANSITION GAMMA	4.795

RF SYSTEM

NUMBER OF STATIONS

1 FOR PROTONS

1 FOR POL PROTONS

2 FOR HEAVY IONS

[where POL== POLARIZED]

HARMONIC NUMBER

3 FOR PROTONS

3 FOR POL PROTONS

3 FOR HEAVY IONS (1 FOR RHIC)

FREQUENCY RANGE (MHz)

FOR PROTONS 2.5 - 3.9

FOR POL PROTONS 2.5 - 3.9

FOR HEAVY IONS 0.178 - 2.5 (.06 - .84 FOR RHIC)

PEAK RF VOLTAGE [KV]

FOR PROTONS 35

FOR POL PROTONS 35

FOR HEAVY IONS 17

ACCELERATION TIME [M-SEC]

FOR PROTONS 50

FOR POL PROTONS 50

FOR HEAVY IONS 500

REPETITION RATE

FOR PROTONS 10 Hz (4 PULSES/AGS PULSE)
 FOR POL PROTONS 1 Hz (1 PULSE/AGS PULSE)
 FOR HEAVY IONS 1 Hz (1 PULSE/AGS PULSE)

DIPOLES

[DIPOLES ARE CURVED AND WEDGED FOR 0 ENTRANCE ANGLE]

NUMBER 36
 LENGTH (MAGNETIC) 2.4 M
 GAP 82.55 MM
 GAP VACUUM CHAMBER 66 MM
 GOOD FIELD REGION ($<10^{-4}$) 16 X 6.6 CM

INJECTION FIELD [KG]

FOR PROTONS 1.56
 FOR POL PROTONS 1.56
 FOR HEAVY IONS 0.105 A/Q

[Q is the charge of the Heavy Ions, (whether fully stripped or not), delivered from the Tandem.]

EJECTION FIELD [KG]

FOR PROTONS 4.0
 FOR POL PROTONS 4.0
 FOR HEAVY IONS 12.0

LAMINATION THICKNESS 1.5 MM
 [0.6 MM AROUND ENDS]

QUADRUPOLES

 NUMBER 48
 LENGTH (MAGNETIC) 0.50375 M
 APERTURE 16.5 CM
 VACUUM CHAMBER AP. 15.5 CM

[AP.== APERTURE]

INJECTION POLE TIP FIELD [KG]

FOR PROTONS 1.02
 FOR POL PROTONS 1.02
 FOR HEAVY IONS 0.068 A/Q

[Q is the charge of the Heavy Ions, (whether fully
 stripped or not), delivered from the Tandem.]

EJECTION POLE TIP FIELD [KG]

FOR PROTONS 2.7
 FOR POL PROTONS 2.7
 FOR HEAVY IONS 7.9

LAMINATION THICKNESS 0.6 MM

FIELD QUALITY

SEXTUPOLE HARMONIC 0.0
 (6 θ / 2 θ) (SHAPE POLE TIP TO ELIMINATE)
 ALL OTHER HARMONICS < 10^{-4}

MAX. VACUUM PRESSURE (N2 EQU.) 10^{-10} TORR

MAX. INTENSITY (PARTICLES PER PULSE)

FOR PROTONS	$1 - 1.5 \times 10^{13}$
FOR POL PROTONS	10^{12}
FOR HEAVY IONS	$2 \times 10^{11} / Z.$

Acknowledgement:

We thank E. Courant, and other members of the Booster Design study group for discussions and Ms. K. Brown for our drawings.




Fig. 1 The Booster Lattice

0 5
METERS
NOTE: ALL DIMENSIONS ARE IN METERS