

BNL-104582-2014-TECH

AGS/AD/Tech Note No. 154;BNL-104582-2014-IR

H5 BEAM KICKER NOSE BUMP AND COIL POSITION DETERMINATION

J. G. Cottingham

May 1979

Collider Accelerator Department Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Accelerator Department BROOKHAVEN NATIONAL LABORATORY Associated Universities, Inc. Upton, New York 11973

AGS DIVISION TECHNICAL NOTE

No. 154

H5 BEAM KICKER NOSE BUMP AND COIL POSITION DETERMINATION

J.G. Cottingham

May 1, 1979

A series of computer relaxation calculations were run to determine an acceptable nose coil position and nose bump configuration of the planned H5 kicker.

The computer program used was an adaptation of a relaxation program written previously by the author to handle electrostatic problems. This adaptation treats the field as a scale potential and is limited to the case of thin coils and infinite permeable cores.

The results are shown in the following figures.

Figure 1 shows the effect of raising the noise coil away from the gap edge. The fringing flux adds to the total flux and as a result increased the inductance with resulting increases in driving voltage. The integral under the curves of Figure 1 yield total flux and thus the inductance of the H5 kicker. Results are summarized in Table I.

Table I

	Normalized	Inductance
		Change
Calculated with assumed 1/2 gap sq. fringe field	1.0	• 0
Nose coil, $h = 0$	•939	-6.1%
Nose coil, $h = .083$ in.	•958	-4.2%
No nose coil, back core return	1.263	+26.3%

Figure 2 and 3 show on an expanded scale the field shape near the ferrite edge. Ferrite bumps of unit height are summarized in Figure 2. Better results are obtained with bumps two units high as shown in Figure 3. The optimum choice is a judgment. I can recommend either the set labeled (2+3) or the set (3+4). The latter set has a small overshoot, less than 1/2%, and extends the field edge relative to the core edge by 0.005 inches. The ferrite bump is a little wider (.042 in. against .003 in.) and thus a little stronger mechanically.

/lsk

Distr. Dept. Admin. AGS Division EE's AGS Division ME's H. Weisberg W. Weng







HC CONTROLS COR

-10 X 10 TO THE CENTIMETER

110

125