

THOUGHTS ON MULTIPLE PULSE INJECTION INTO THE AGS BOOSTER FROM AN EBIS SOURCE

Y. Y. Lee

July 1992

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy
USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No. DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Accelerator Division
Alternating Gradient Synchrotron Department
BROOKHAVEN NATIONAL LABORATORY
Upton, New York 11973

Accelerator Division
Technical Note

AGS/AD/Tech. Note No. 362

**THOUGHTS ON MULTIPLE PULSE INJECTION INTO THE
AGS BOOSTER FROM AN EBIS SOURCE**

Y.Y. Lee

July 6, 1992

AGS/AD/Tech. Note No. 361 raised the possibility of injecting into the AGS Booster from an EBIS source and heavy ion linac combination. While leaving the output energy of the linac as a free parameter, the note concluded that the optimum charge state of the ions is 39 for gold and 54 for uranium. The conclusion is based on the number of ions in the EBIS source and the stripping efficiency between the Booster and the AGS. In this note, we are going to examine the possibility of injecting multiple pulses into the Booster and its implications for longitudinal phase space.

Stacking into the momentum space of the synchrotron has been accomplished at the CERN ISR and also in the booster synchrotron MIMAS of the SATURN at CEN Saclay.¹ In principle, the momentum space stacking is twice as efficient as betatron space. A momentum space stacking is done in the following way. After the first turn is injected, the injected beam is moved to a lower energy orbit of the synchrotron, leaving the original orbit for the next pulse to be injected. This can be accomplished in two ways; namely, by decelerating the injected beam or raising the magnetic field of the machine to raise the central energy of the synchrotron. For the last case, the injection energy has to be changed to an appropriate value for the next injection pulse. At MIMAS, the deceleration is accomplished by ramping the magnetic flux in the toroidal core around the beam, thus providing betatron deceleration.

Because the output energy of the heavy ion linac can be changed by varying the phase of the rf in the linac cavities, the second method could be more suitable for the AGS Booster. Let us examine multi-pulse injection into the horizontal admittance of the Booster. The Booster horizontal admittance can be defined as a 2-inch aperture at the horizontal beta maximum that is at the middle of the horizontal quadrupoles (13.66 m).

Instead of discussing general terms, we would like to analyze a specific case to see what can be accomplished. We have chosen the following ion to study injection and capture:

Ion Species	Gold
Charge State (Q)	39
Energy	2.36 MeV/u
Normalized Emittance	0.25π mm-mr
Unnormalized Emittance	3.52π mm-mr

The energy is such that the proton cavity of the Booster should be able to capture at the 24th harmonic. The normalized emittance is obtained from the EBIS source at MIMAS. At the downstream end of the injection septum of the AGS Booster, we have the following parameters:

Horizontal Beta	12.2 m
Horizontal Alpha	-1.848
Dispersion Function	2.66 m
Dispersion Prime	0.3962
Septum Thickness	1 mm

The distance between two successive injections should be 1.4 cm in order to avoid the overlap in the phase space. This distance includes the effect of the septum. We assume the pulse length of the EBIS source to be comparable to the 9.5 microsecond revolution time of the ion in the Booster.

The injection is illustrated in Figure 1. The injection bump is set up to inject the beam in an extreme outer location (Location 7 in the figure). In between the linac pulses, the field of the Booster is raised by 0.53 percent to move the injected beam from Location 7 to Location 6 along the dispersion line, leaving Location 7 open for the next pulse. The next linac pulse must have a momentum 0.53% higher (or kinetic energy 1.03% higher) than the previous pulse. One can continue the process until the first pulse starts to spill out of the inside edge of the acceptance. In principle, up to seven linac pulses can be stacked into the emittance of the Booster.

For adiabatic bunching of the coasting beam, the best energy spread is:

$$\left(\frac{\Delta E}{E}\right)_B = \left(\frac{\Delta E}{E}\right)_I \frac{\pi}{2} = \beta(QeV)^{1/2} \left(\frac{2}{h \eta \pi E}\right)^{1/2}$$

where $(\Delta E/E)_I$ and $(\Delta E/E)_B$ are the energy spread of the injected and bunched beam.

The variables are:

$$\eta = 1/\gamma^2 - 1/\gamma_T^2 = 0.953$$

$$E = \text{total energy of the ion} = 1.839 \times 10^{11} \text{ eV}$$

$$\Delta P/P = 5.3 (n-1) \times 10^{-3} \quad n = \text{number of injected pulses } n > 1$$

$$\beta = v/c = 0.07077$$

$$h = \text{harmonic number}$$

$$Q = \text{ion charge} = 39$$

$$\begin{aligned} eV &= \frac{\pi^3 \beta^2 h \eta E}{8 Q} \left(\frac{\Delta P}{P}\right)_I^2 \\ &= 0.6045 h (n-1)^2 \end{aligned}$$

This would be the required rf voltage and the resulting bunch area would be:

$$S = (h Q eV)^{1/2} \frac{16 \beta}{h} \left(\frac{E}{2 \pi \eta}\right)^{1/2} \text{ eV-rad}$$

$$= \frac{(h Q eV)^{1/2}}{2 \pi f_0 h} \frac{16 \beta}{h} \left(\frac{E}{2 \pi \eta}\right)^{1/2} \text{ eV-sec}$$

where f_0 is the rotation frequency of the ion in the Booster.

$$S = \frac{2\beta^2 E}{h f_0} \left(\frac{\Delta P}{P} \right)_I = \frac{2\beta E}{h f_{\text{rev}}} \left(\frac{\Delta P}{P} \right)_I$$

$$= 46.08 (n-1)/h \text{ eV-sec}$$

$$S/u = 0.2339 (n-1) \text{ eV-sec/u}$$

Table I summarizes the results.

Table I				
No. of Injected Pulses	RF Voltage (kV)		Bucket Area (ev-sec/u)	
	h = 3	h = 24	h = 3	h = 24
2	1.81	14.51	0.078	0.010
3	7.25	58.03	0.156	0.019
4	16.30	130.60	0.234	0.029
5	29.00	232.10	0.312	0.039

Although one can inject into the Booster up to 7 linac pulses, the lack of rf voltage limits the number of pulses stacked into the momentum space. The present rf system limits the number to 3-4 pulses per cycle.

I would like to thank Krsto Prelec for mentioning this possibility and for many valuable discussions.

Reference

1. J.C. Ciret, et al., Proc. EPAC 88, p. 812, 1988.

MOMENTUM STACKED 2.36 MEV/U BEAM PULSES

WITH ADMITTANCE OF BOOSTER AT INJ. POINT

