

TEVATRON STUDIES REPORT

E. C. Raka

December 1992

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No. DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Accelerator Division
Alternating Gradient Synchrotron Department
BROOKHAVEN NATIONAL LABORATORY
Upton, New York 11973

Accelerator Division
Technical Note

AGS/AD/Tech. Note No. 369

TEVATRON STUDIES REPORT

G. Jackson, D. McConnell, and B. Fellenz
Fermi National Accelerator Laboratory

E. Raka and S.P. Yamin
Brookhaven National Laboratory

December 3, 1992

Introduction

On Wednesday, July 24, 1991, we studied the effectiveness of "constant amplitude" transverse damping at the Fermilab Tevatron. In this mode of damping, whenever a bunch's displacement exceeds a specified threshold, a constant (usually maximum) amplitude correction pulse is applied to the damper kicker. This is in contrast to the "linear" mode, where the kick is proportional to the displacement.

Procedure

The beam was injected into the Tevatron with vertical displacement, so as to induce vertical betatron oscillations. Figure 1 shows the output of one of the pick-up electrodes (PUEs) for 1024 successive turns. The modulation is caused by the changing coherence of the oscillations of particles of different momenta (and tune because of the chromaticity) around the synchrotron oscillation cycle. Decoherence is responsible for the damping of the oscillations. If we assume that, then the amplitude is given by $A = A_0 \exp[-(\text{turn } \#)/k]$, $k = 2661$ turns.

We next studied the properties of various damping transfer functions. These are shown in Figures 2a-2d. In all cases the abscissa represents displacement from the "closed orbit" in millimeters and the ordinate the voltage applied to the kicker electrodes (± 1000 V maximum).

First we studied linear damping (Figure 2a). The results are shown in Figure 3. Here, we get $k = 1089$ turns.

For the mixed constant-amplitude and linear transfer function shown in Figure 2b, we got the results shown in Figure 4. The fit to the damping constant gives $k = 739$ turns.

A constant amplitude transfer function with the threshold set at ± 2.5 mm is shown in Figure 2c and the results are plotted in Figure 5. $k = 1002$ turns.

Constant-amplitude damping with a ± 1 mm transfer function threshold is shown in Figure 2d. These results are given in Figure 6. $k = 797$ turns.

Conclusions

We believe that we have shown that constant-amplitude damping can be as effective as linear damping in the Tevatron. However, since this machine operates in a regime in which resistive wall instabilities are not present and where the Landau damping is sufficient, the present studies do not represent an adequate test. We suggest extending these tests to the Main Ring, where there is a resistive wall instability. Unfortunately, this will require modifying more than software.







FIGURE 1 - NO DAMPING




(a)



(b)



(c)



(d)

FIGURE 2 - TRANSFER FUNCTIONS




FIGURE 3- LINEAR DAMPING




FIGURE 4 - MIXED LINEAR/CONSTANT DAMPING




FIGURE 5 - CONSTANT AMPLITUDE (± 2.5 mm) DAMPING




FIGURE 6 - CONSTANT AMPLITUDE (± 1 mm) DAMPING