



BNL-104618-2014-TECH

AGS/AD/Tech Note No. 190;BNL-104618-2014-IR

# CHROMATICITY CORRECTION SEXTUPOLES FOR THE AGS

Y. Y. Lee

October 1983

Collider Accelerator Department  
**Brookhaven National Laboratory**

**U.S. Department of Energy**

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

## **DISCLAIMER**

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Accelerator Department  
BROOKHAVEN NATIONAL LABORATORY  
Associated Universities, Inc.  
Upton, New York 11973

AGS Division Technical Note  
No. 190

CHROMATICITY CORRECTION SEXTUPOLES FOR THE AGS

Y.Y. Lee

October 24, 1983

At present, there are two sets of 12 sextupoles in 7 (vertical) and 13 (horizontal) straight sections. They were originally intended for chromaticity correction.<sup>1</sup> They, however, generate a third integral resonance at the 24th harmonic which is a super structural resonance, and the usefulness of the sextupoles is limited.

In this note, we would like to propose a solution to the problem. Suppose we add four more sets of sextupoles (two each for horizontal and vertical) and eliminate the 24th harmonic components. The other components like 25, 26, and 27 are automatically taken care of.

1. Horizontal

In addition to 13 straight sections, place sextupoles in 2-foot straight sections 1 and 9. The  $\beta$  and  $\alpha$  are horizontal maximum at those points. If one goes through mathematics one finds the relationships

$$\left( \begin{smallmatrix} \ell & B'' \\ 9 & 9 \end{smallmatrix} \right) = 1.1 \left( \begin{smallmatrix} \ell & B'' \\ 13 & 13 \end{smallmatrix} \right)$$

$$\left( \begin{smallmatrix} \ell & B'' \\ 1 & 1 \end{smallmatrix} \right) = -0.57 \left( \begin{smallmatrix} \ell & B'' \\ 13 & 13 \end{smallmatrix} \right)$$

eliminate the 24th harmonics and

---

<sup>1</sup>Accelerator Department Internal Report EDC-26, 1957.

gives a total integrated sextupole strength of 1.63 ( $\int B''_{13}$ ). The total sextupole strength required is determined from

$$\begin{aligned} \frac{\Delta Q}{Q} &= \left[ \frac{1}{4 \pi Q} \int \frac{B''(s) \beta(s) \alpha(s) ds}{B \rho} \right] \frac{\Delta P}{P} \\ &= \frac{1}{4 \pi Q} \beta(s) \alpha(s) \int \frac{\int B''(s)}{B \rho} \cdot \frac{\Delta P}{P} \end{aligned}$$

Taking  $\beta(s) = 22$  m

$$\alpha(s) = 2$$
 m

$$Q = 8.7$$

$$\frac{\Delta Q}{Q} / \frac{\Delta P}{P} \cong 7.87 \frac{\int B''_{13}}{B \rho}$$

If one wants  $\frac{\Delta Q}{Q} / \frac{\Delta P}{P} = 1$ ,

$$\int B''_{13} = \frac{B \rho}{7.87}$$

and at 10 GeV/c ( $B \rho \sim 36.4$ )

$$\int_{13} B''_{13} = 4.63$$
 T/M.

That means at 9 straight sections

$$\int_9 B''_9 = 5.1$$
 T/M.

Consider making 7" diameter 10 cm long sextupole

$$B''_9 = 51$$
 T/M<sup>2</sup>

and pole tip field becomes

$$B_T = 0.4$$
 T.

## 2. Vertical

Consider three sets of sextupoles at 7, 11 and 19 straight sections; required field relations are

$$\left( \begin{matrix} \ell_{11} & B''_{11} \end{matrix} \right) = 0.915 \left( \ell B''_7 \right)$$

$$\left( \begin{matrix} \ell_{19} & B''_{19} \end{matrix} \right) = - 0.55 \left( \ell_7 B''_7 \right)$$

and required strengths are similar to the horizontal sets.

Since the field strength suggests one should have iron core magnets, a careful study of interference with the main magnetic field is required. When the sextupoles are also used for other stopband correction, the relationship should be kept in order not to create stopband at the 24th harmonic.

mvh

Distribution: AD S&P