



Brookhaven
National Laboratory

BNL-105785-2014-TECH

EP&S No. 72;BNL-105785-2014-IR

Optics of Beam #B5

D. G. Ryan

September 1974

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.AT(30-1)-16 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

BROOKHAVEN NATIONAL LABORATORY
Associated Universities, Inc.
Upton, New York

EP&S DIVISION TECHNICAL NOTE

No. 72

D.G. Ryan

September 9, 1974

OPTICS OF BEAM #B5

Introduction

Three beams now share the B target station; MESB, B1, and B5. It will be assumed that a tight focus must always be maintained at B for proper operation of the MESB. The remaining beams, B1 and B5, share common elements in such a way that B5 cannot be operated unless B1 is set to negative polarity above a momentum of ~ 8 GeV/c.

B1 - B5 Sharing

1. Settings - The settings of the exclusive optical elements of beam #B5 have been recalculated due to the downstream movement of the B' target station by 15 inches. Table I lists the currents, shunt readings, and computer counts for the three compatible running conditions of B1; 8, 12, and 20 GeV/c negative polarity (note that 100 mv shunt reading \equiv 4000 computer counts).

2. Transmission - Figures 1 - 3 show ray traces for the above mentioned running conditions. The rays plotted are ± 1 mr horizontally, ± 1 mr vertically, and $\pm 1\% \Delta p/p$. Limiting apertures of ± 1.375 in.

horizontally in Q7 and ± 0.75 in. vertically at the downstream end of the wall have been used to calculate the acceptances listed in Table II.

As there are no direct measurements of the proton beam divergence at the B target, we have done a reverse ray trace from the target to an upstream flag and this is shown in Figure 4. The beam size as measured by the flag is consistent with divergences of ± 2 mr horizontally and ± 5 mr vertically at the B target. Using these figures, the transmissions from B to B' have been calculated and are given in Table II. Also

given in Table II are the transmissions with a 2-in. tungsten target. This attenuates the proton beam by 50%, and introduces 2 mr of multiple scattering.

B5 Exclusively

1. Settings - Maximum transmission from B to B' is achieved when B5 has control of all the common transport elements. The calculated settings for this case are given in Table III. Magnet D1 must have a 2% ramp to compensate for the change in beam momentum. If no ramp is installed, the settings are the same except that the polarities of Q6 and Q7 should be reversed.
2. Transmission - Figure 5 shows a ray trace for the case where magnet D1 is ramped. The rays plotted are ± 2 mr horizontally, ± 5 mr vertically, and 1% $\Delta p/p$. The limiting apertures are ± 1.375 in. horizontally in Q6, and ± 0.75 in. vertically in the wall. Acceptances and transmissions both for this case and for when D1 is not ramped are given in Table II.

Conclusion

Optimum transmission to the B' target station is achieved when B5 has exclusive control of all magnets between B and B'. Compatible running of B5 and B1 is possible when B1 is set to negative polarity and the intensity requirement at the B' target station is $\sim 2 \times 10^{10}$ protons per pulse.

Distribution: Admin.
EP&S Div.

TABLE I
 B1 Compatible Settings of B5

B1 Momentum (GeV/c Negative Polarity)	Magnet	Polarity	Current (amps)	Shunt (mv)	Computer (counts)
20	D3	A	2154	53.85	2154
	D4	B	240	30.00	1200
	Q6	B	1551	51.70	2068
	Q7	A	2157	71.90	2876
	P1 D5	as required B	as required 2750	68.75	2750
12	D3	B	836	20.90	836
	D4	A	91	11.40	455
	Q6	B	1663	55.43	2217
	Q7	A	2273	75.77	3031
	P1 D5	as required B	as required 2750	68.75	2750
8	D3	B	2347	58.68	2347
	D4	A	261	32.60	1305
	Q6	B	1683	56.10	2244
	Q7	A	2291	76.37	3055
	P1 D5	as required B	as required 2750	68.75	2750

TABLE II

Transmission to B' Target

B1 Momentum (GeV/c)	8	12	20	B5 Only (D1 ramped)	B5 Only (No ramp)
Acceptance (mr H x mr V)	$\pm 0.60 \times \pm 0.55$	$\pm 0.70 \times \pm 0.60$	$\pm 1.2 \times \pm 0.95$	$\pm 1.8 \times \pm 4.9$	$\pm 1.2 \times \pm 4.9$
Transmission to B' (no target at B)	3%	4%	11%	88%	59%
Transmission to B' (2" W target at B)	1%	1.5%	4%	29%	19%

TABLE III

Exclusive Settings for B5

Magnet	Polarity	Current (amp)	Shunt (mv)	Computer (counts)
Q1	B	2465	61.63	2465
Q2	B	2465	61.63	2465
Q3	B	2469	61.73	2469
Q4	A	1489	59.56	2382
Q5	A	1489	59.56	2382
D1	B	1070	26.75	1070
D2	B	1070	26.75	1070
D3			Off	
D4			Off	
Q6	AA	1488	49.60	1984
Q7	B	2002	66.73	2669
P1		As required		
D5	B	2750	68.75	2750

NOTE: If D1 is not ramped, reverse polarities of Qy and Q7.

XMAX	DX1	YMAX	DY1	P	DP
4.000	0.00100	4.000	0.00100	28.500	0.010
	1 mr		1 mr		1 %

```

0.036 0.072 0.108 0.144 0.180 0.216 0.245 0.266 0.277 0.279 0.286 0.302 0.326 0.356 0.387 0.418 0.448 0.479 0.509 0.540 0.571 0.601 0.632 0.662 0.693 0.723 0.754 0.785 0.815 0.846 0.876 0.907 0.938 0.968 0.999 1.029 1.060 1.090 1.121 1.152 1.182 1.213 1.243 1.274 1.304 1.334 1.364 1.394 1.424 1.454 1.484 1.514 1.544 1.574 1.604 1.634 1.664 1.694 1.724 1.754 1.784 1.814 1.844 1.874 1.904 1.934 1.964 1.994 2.024 2.054 2.084 2.114 2.144 2.174 2.204 2.234 2.264 2.294 2.324 2.354 2.384 2.414 2.444 2.474 2.504 2.534 2.564 2.594 2.624 2.654 2.684 2.714 2.744 2.774 2.804 2.834 2.864 2.894 2.924 2.954 2.984 3.014 3.044 3.074 3.104 3.134 3.164 3.194 3.224 3.254 3.284 3.314 3.344 3.374 3.404 3.434 3.464 3.494 3.524 3.554 3.584 3.614 3.644 3.674 3.704 3.734 3.764 3.794 3.824 3.854 3.884 3.914 3.944 3.974 4.004 4.034 4.064 4.094 4.124 4.154 4.184 4.214 4.244 4.274 4.304 4.334 4.364 4.394 4.424 4.454 4.484 4.514 4.544 4.574 4.604 4.634 4.664 4.694 4.724 4.754 4.784 4.814 4.844 4.874 4.904 4.934 4.964 4.994 5.024 5.054 5.084 5.114 5.144 5.174 5.204 5.234 5.264 5.294 5.324 5.354 5.384 5.414 5.444 5.474 5.504 5.534 5.564 5.594 5.624 5.654 5.684 5.714 5.744 5.774 5.804 5.834 5.864 5.894 5.924 5.954 5.984 6.014 6.044 6.074 6.104 6.134 6.164 6.194 6.224 6.254 6.284 6.314 6.344 6.374 6.404 6.434 6.464 6.494 6.524 6.554 6.584 6.614 6.644 6.674 6.704 6.734 6.764 6.794 6.824 6.854 6.884 6.914 6.944 6.974 7.004 7.034 7.064 7.094 7.124 7.154 7.184 7.214 7.244 7.274 7.304 7.334 7.364 7.394 7.424 7.454 7.484 7.514 7.544 7.574 7.604 7.634 7.664 7.694 7.724 7.754 7.784 7.814 7.844 7.874 7.904 7.934 7.964 7.994 8.024 8.054 8.084 8.114 8.144 8.174 8.204 8.234 8.264 8.294 8.324 8.354 8.384 8.414 8.444 8.474 8.504 8.534 8.564 8.594 8.624 8.654 8.684 8.714 8.744 8.774 8.804 8.834 8.864 8.894 8.924 8.954 8.984 9.014 9.044 9.074 9.104 9.134 9.164 9.194 9.224 9.254 9.284 9.314 9.344 9.374 9.404 9.434 9.464 9.494 9.524 9.554 9.584 9.614 9.644 9.674 9.704 9.734 9.764 9.794 9.824 9.854 9.884 9.914 9.944 9.974 10.004
    
```

Figure 2. B5 with B1 at 12GeV/c

B5BEAM 08/27/74



XMAX	DX1	YMAX	DY1	P	DP	I %
4.000	0.00100	4.000	0.00100	28.500	0.010	
1 m						
0.036						XIY
0.072						XIY
0.108						XI-Y
0.144						XI-Y
0.180						XI-Y
0.216	Q1					XI-Y
0.240						XI-Y
0.252	Q2					XI-Y
0.248	Q3					XI-Y
0.230	Q4					XI-Y
0.219	Q5					XI-Y
0.218						XI-Y
0.228	Q5					XI-Y
0.246						XI-Y
0.263						XI-Y
0.281						XI-Y
0.299						XI-Y
0.316						XI-Y
0.334						XI-Y
0.351						XI-Y
0.369	D1					XI-Y
0.386	D2					XI-Y
0.404	D2					XI-Y
0.422						XI-Y
0.439						XI-Y
0.457						XI-Y
0.474	D3					XI-Y
0.492	D3					XI-Y
0.509						XI-Y
0.527	WALL					XI-Y
0.545	WALL					XI-Y
0.562	WALL					XI-Y
0.580	WALL					XI-Y
0.597	WALL					XI-Y
0.615	WALL					XI-Y
0.632	WALL					XI-Y
0.650	WALL					XI-Y
0.668	WALL					XI-Y
0.685	WALL					XI-Y
0.703	WALL					XI-Y
0.720	WALL					XI-Y
0.738	D4					XI-Y
0.755						XI-Y
0.793	Q6					XI-Y
0.981						XI-Y
1.177	Q7					XI-Y
1.100						XI-Y
0.942						XI-Y
0.785						XI-Y
0.628						XI-Y
0.471						XI-Y
0.314						XI-Y
0.157						XI-Y
-0.000						XIY

Figure 3. B5 with B1 at 20GeV/c

0.036
0.072
0.108
0.144
0.180
0.216
0.263
0.326
0.407
0.512
0.600
0.660
0.686
0.691
0.695
0.699
0.703
0.708
0.712
0.716
0.720
0.724
0.728
0.732
0.735
0.739
0.743
0.746
0.750
0.753
0.757
0.760
0.764
0.767
0.771
0.774
0.778
0.781
0.784
0.788
0.791
0.795
0.798
0.781
0.620
0.440
0.362
0.310
0.258
0.207
0.155
0.103
0.052
-0.000

B5BEAM 08/27/74

