

## Multipole Polarities for the SNS Accumulator Ring

S. Tepikian

July 2002

Collider Accelerator Department  
**Brookhaven National Laboratory**

**U.S. Department of Energy**

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.DE-AC02-98CH10886 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

## **DISCLAIMER**

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



## ***Multipole Polarities for the SNS Accumulator Ring***

BNL/SNS TECHNICAL NOTE

NO. 114

S. Tepikian, C.J. Gardner

July, 2002

COLLIDER-ACCELERATOR DEPARTMENT  
BROOKHAVEN NATIONAL LABORATORY  
UPTON, NEW YORK 11973

# Multipole Polarities for the SNS Accumulator Ring

S. Tepikian, C. J Gardner



July, 2002




## Introduction

We document polarities of the magnet multipoles. In this paper we extend the definitions for the polarities given by [1]. For dipoles in the ring — which uses proton beam — a bend toward the right (in the negative  $X$  direction) has a **B** polarity. Note, the convention was established for the HEBT line which uses  $H^-$  beam. Furthermore, quadrupoles with with polarity **A** defocus the beam horizontally.

## Field Layout

The magnetic field lines for the multipoles are shown in the following schematics. The skew multipoles are obtained by rotating regular multipoles in the clockwise direction. The coordinate systems is shown in Fig. 1, where  $X$  is the radial direction,  $Y$  is the vertical direction and  $Z$  is along the beam. Fig. 2 shows the regular and skew dipoles, Fig. 3 shows the quadrupoles, Fig. 4 shows the sextupole fields and finally, Fig. 5 shows the octupoles.





From the direction of the field lines given in the Figs. 2-5, the relation between the multipoles and the planar magnet field are as follows[2]:

$$\mathbf{B}_y(x, 0, z) = - \sum_{n=0}^{\infty} B_n^{[SNS]}(z) \frac{x^n}{n!} \quad \mathbf{B}_x(x, 0, z) = \sum_{n=0}^{\infty} A_n^{[SNS]}(z) \frac{x^n}{n!}$$

where,  $B_n^{[SNS]}(z)$  are the regular multipole strengths and  $A_n^{[SNS]}(z)$  are the skew multipole strengths. Note, the negative sign for the regular multipoles, due to the choice of field directions. Next we will consider the field directions used in the optics design.

## Optics Design

To find out the field directions for the multipoles in the MAD [3]<sup>1</sup> program, a simple beam line with a drift space followed by the multipole (excited with a positive strength) then another drift space was created (see the Appendix). The closed orbit then is observed for a particle with an offset of +1cm through this line, to see in which direction the particle is shifted (For the dipole, use the survey command). From the direction of the shift, the field direction is deduced. The results are shown in Table 1.

	<b>+X Bump (1 cm)</b>			
<b>Device</b>	<b>X shift</b>	<b>Y shift</b>	<b>Field Direction</b>	<b>Polarity</b>
Dipole	-	0	↑	B
Skew Dipole	0	-	→	B
Quadrupole	-	0	↑	B
Skew Quadrupole	0	-	→	B
Sextupole	-	0	↑	B
Skew Sextupole	0	-	→	B
Octupole <sup>2</sup>	-	0	↑	B
Skew Octupole <sup>2</sup>	0	-	→	B

Table 1: Using MAD, an orbit bump in the X direction was applied to each device (Col. 1) with a positive strength. The shift in the closed orbit is then determined: -, 0 or + (shown in Cols. 2 and 3). Assuming a proton beam, the field direction at the +X position is shown in Col. 4. From the field direction, we deduce the polarity in Col. 5.

This leaves the relation between the MAD multipoles and the planar magnetic fields as:

$$\mathbf{B}_y(x, 0, z) = \sum_{n=0}^{\infty} B_n^{[MAD]}(z) \frac{x^n}{n!} \quad \mathbf{B}_x(x, 0, z) = - \sum_{n=0}^{\infty} A_n^{[MAD]}(z) \frac{x^n}{n!}$$

1 MAD versions 8.22/12 and 8.23/0 gave these results. Other versions of MAD may be different.

2 For octupoles, use the MAD "MULTIPOLE" device. "OCTUPOLE" behaves differently.

Thus, we have  $B_n^{[SNS]}(z) = -B_n^{[MAD]}(z)$  and  $A_n^{[SNS]}(z) = -A_n^{[MAD]}(z)$ . This can be expressed with following rule of thumb: “In the SNS accumulator ring, a positive strength (from MAD) for a regular or skew multipole has its power supply set to polarity B”.

## Appendix

Here is the MAD file used to check the multipole field directions:

```

title, "Simple Line"
beam, particle = proton, gamma = 108
oo : drift, l = 1.0
!
! ---- Skew
!bmultx : sbend, angle = 0.01, l = 0.1, tilt
!bmultx : quadrupole, k1 = 0.01, l = 0.1, tilt
!bmultx : sextupole, k2 = 10.0, l = 0.1, tilt
!bmultx : octupole, k3 = 1000.0, l = 0.1, tilt
!bmultx : multipole, k3l = 1000.0, t3
!
! ---- Regular
!bmultx : sbend, angle = 0.01, l = 0.1
!bmultx : quadrupole, k1 = 0.01, l = 0.1
!bmultx : sextupole, k2 = 10.0, l = 0.1
!bmultx : octupole, k3 = 1000.0, l = 0.1
bmultx : multipole, k3l = 1000.0

bline : line=(oo, bmultx, oo)
use, bline
  print, full
  survey
  twiss, x = 0.01, px = 0.0, y = 0.0, py = 0.0, betx = 1.0, bety = 1.0

```

## Acknowledgments

We thank W. Glenn, J. Wei, D. Raparia, Y. Y. Lee, Y. Papaphilippou, N. Tsoupas and R. Lambiase for many fruitful discussions.

## Bibliography

- [1] J. Wei, SNS/AP/08, July 27, 2001
- [2] C. J. Gardner, BNL/SNS/053, November 19, 1998
- [3] H. Grote, F. C. Iselin, CERN/SL/90-13 (AP) (Rev. 4), May 26, 1995