

Momentum Painting in SNS Accumulator Ring

M. Blaskiewicz

August 2003

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.DE-AC02-98CH10886 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



Momentum Painting in SNS Accumulator Ring

BNL/SNS TECHNICAL NOTE

NO. 124

M. Blaskiewicz

BNL, Upton, NY 11973, USA

August 25, 2003

COLLIDER-ACCELERATOR DEPARTMENT
BROOKHAVEN NATIONAL LABORATORY
UPTON, NEW YORK 11973

Momentum painting in SNS accumulator ring

M. Blaskiewicz, C-AD Brookhaven National Laboratory

August 25, 2003

For 2 MW operations, the peak beam current in the SNS accumulator ring approaches 100 A. Collective effects are a significant concern and the various stability thresholds are monotonic functions of the momentum spread of the beam. Therefore, it is useful to have control of the injected momentum distribution. The energy corrector and spreader cavities were included in the design to allow the operations team to tune the rms energy spread of the injected beam, but these devices have been removed from the baseline. The energy corrector cavity runs at the nominal RF frequency. This device is located downstream of the main linac so that the longitudinal phase of the bunches is roughly proportional to their energy deviation. A proper choice of voltage corrects the centroid energy of the individual bunches. Next, the energy spreader cavity runs at a frequency that is offset from the nominal RF frequency by ~ 100 kHz. This device provides a pseudo-random kick to the individual bunches which increases the rms energy spread of the beam without producing the large momentum tails associated with a debuncher cavity.

The energy corrector cavity is difficult to replace, since its operation depends of the correlation between phase and energy offset. On the other hand, the energy spreader cavity requires no drift. This opens the possibility of modifying the last accelerating cell of the superconducting linac for operation in energy spreader mode. Near the end of the superconducting linac, each cavity increases the beam energy by ≈ 15 MeV [1]. The energy spreader cavity requires $\lesssim 5$ MeV so a single superconducting cavity could supply the necessary voltage. The mechanical tuners allow for ≈ 200 kHz of frequency swing [2] and the 3 dB bandwidth of the klystrons is ± 1.3 MHz [3]. Both of these are comfortably larger than the required 100 kHz frequency offset.

The external Q of the fundamental power couplers is 7.0×10^5 [4] which gives a frequency offset of $f_{res}/2Q = 575$ Hz at the half power point. Therefore, modification of the fundamental power coupler is required.

References

- [1] J. Stovall, J.H. Billen, S. Nath, H. Takaneda, L.M. Young, D. Jeon, K.R. Crandall, R. Shafer, PAC01, p 446 (2001).
- [2] J. Preble et.al. , PAC03.
- [3] S. Lenci, E. Eisen, B. Stockwell PAC03
- [4] Y. Kang *et al* PAC01 p 1122