



BNL-105620-2014-TECH

BNL/SNS Technical Note No. 051;BNL-105620-2014-IR

# SNS Accumulator Ring Extraction Fast Kicker Modulator Initial Simulation

J. Mi

September 1998

Collider Accelerator Department  
**Brookhaven National Laboratory**

**U.S. Department of Energy**

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.DE-AC02-98CH10886 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

## **DISCLAIMER**

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



# **SNS Accumulator Ring Extraction Fast Kicker Modulator Initial Simulation**

BNL/SNS TECHNICAL NOTE

NO. 051

Jianlin Mi

September 25, 1998

ALTERNATING GRADIENT SYNCHROTRON DEPARTMENT  
BROOKHAVEN NATIONAL LABORATORY  
UPTON, NEW YORK 11973

# SNS Accumulator Ring Extraction Fast Kicker Modulator Initial Simulation

Jianlin Mi  
AGS Department,  
Brookhaven National Laboratory

September 25, 1998

## 1. Introduction

The fast kicker is used for extracting the beam, from the accumulator ring, in a single turn taking place in less than one beam revolution period of approximately 800nS, very soon after the injection stacking process is completed. The accumulated beam will have a gap of 250 nS to enable the magnetic field in the fast kicker to rise its extraction level within this gap. The fast kicker system consists of eight or more sections of ferrite core magnets. A pulse-forming network (PFN) is discharged into a single - turn ferrite core magnet by a fast ceramic thyratron, which is trigger by a ring radio frequency (rf) synchronized time trigger.

## 2. Kicker requirements

The requirements for the SNS extraction kicker are given in the SNS Design Report. section 5.11 (WBS 1.5.9). The main parameters are:

Vert deflection angle	16.8 mrad
Gap (H × V)	11.5cm × (12.9 ~ 15.4cm)
Length of F <sub>e</sub> section	37cm ~ 44 cm

## 3. Kicker magnet initial electric parameters

For an eight (8) section kicker magnet, the following parameters are obtained.

Kicker magnet inductance	1.1	μH
Peak current	2.8	kA
Pulse repetition rate	60	Hz
Rise time	200	nS
Pulse flattop	600	nS

Fall time	N.A.
Magnet sections	8
Re- charging time 12 ~ 14	mS

#### 4. Kicker modulator simulation

The simulation of the fast kicker modulator consists of a pulse-forming network (PFN), a switch (SW), kicker inductor ( $L_k$ ) and a resistor (R). The PFN is a equal capacitance pulse forming network which consists of twenty LC sections. The impedance of the PFN is  $6\Omega$ . The simulation parameters are following:

PFN section	20
Load inductance: $L_K$	1.10 $\mu$ H
Load resistance R	6 $\Omega$
PFN capacitance $C_0$	4.15 nF
PFN inductance $L_0$	0.15 $\mu$ H
PFN impedance $Z_0$	6 $\Omega$
Charging voltage	34 kV
Peak current	2.8 kA
Rise time	<200 nS
Pulse flattop:	700 nS

This simulation waveform of the kicker magnet current is shown in Fig 1. The vertical scale is current /100 and the horizontal scale is simulation time in  $\mu$ sec. The peak current shown is 2845 Amperes.

NS80413A.CIR Temperature = 27

