

BNL-105650-2014-TECH

BNL/SNS Technical Note No. 082;BNL-105650-2014-IR

Closed Orbit Distortion and Correction in the 248 Meter SNS Accumulator Ring Lattice

C. J. Gardner

July 2000

Collider Accelerator Department Brookhaven National Laboratory

# **U.S. Department of Energy**

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.DE-AC02-98CH10886 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

## DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



# Closed Orbit Distortion and Correction in the 248 Meter SNS Accumulator Ring Lattice.

# BNL/SNS TECHNICAL NOTE

NO. 082

C.J. Gardner

July 18, 2000

COLLIDER-ACCELERATOR DEPARTMENT BROOKHAVEN NATIONAL LABORATORY UPTON, NEW YORK 11973

# Closed Orbit Distortion and Correction in the 248 Meter SNS Accumulator Ring Lattice.

C.J. Gardner

July 18, 2000

The SNS accumulator ring lattice has evolved considerably since the last calculations [1] of COD (Closed Orbit Distortion) and Correction were done. Following are the results of similar calculations for the current lattice.

## **1** Lattice Parameters

The current lattice is described in Reference [2]. The elements and layout for one superperiod are shown in Figure 1. Figure 2 shows the Beta Functions and Dispersion for one superperiod. (Here the plot starts at the downstream end of quadrupole QVX9.) Figure 3 shows the same for the entire 248 meter lattice (four superperiods). The horizontal and vertical tunes are  $Q_H = 6.3$  and  $Q_V = 5.8$ .

#### 2 Calculation of COD

We consider the COD due to random errors in the horizontal and vertical placement of the lattice quadrupoles. The error distribution is assumed to be Gaussian with RMS values  $\sigma_H = \sigma_V = 0.25$  mm for the horizontal and vertical positions. The MAD code was used to calculate the COD for each of 101 separate distributions of placement errors. A cut-off of  $2.5 \sigma$  was imposed for each distribution (i.e. any errors greater than 2.5 times the RMS value were rejected). The tunes were set to be  $Q_H = 6.3$  and  $Q_V = 5.8$ .

#### **3** Correction of COD

The method of 3-bumps [1, 3, 4] was used to correct the COD for each distribution of quadrupole placement errors. Here, as derived in Ref. [3], the kick required in the *j*th corrector is given by

$$\phi_j = \left\{ \frac{M_{11}^{(j)}}{M_{12}^{(j)}} + \frac{M_{22}^{(j-1)}}{M_{12}^{(j-1)}} \right\} Y_j - \frac{Y_{j-1}}{M_{12}^{(j-1)}} - \frac{Y_{j+1}}{M_{12}^{(j)}}$$
(1)

where  $M_{kl}^{(j)}$  are the matrix elements of the transfer matrix from the *j*th to the (j + 1)th corrector, and  $Y_j$  is the value of the uncorrected COD at the *j*th corrector. The correctors are treated as point dipoles located 10 centimeters from the ends of the quadrupoles. (The dipole correctors are labeled DVCX1, DHCX2, DVCX3, DHCX4, ..., and so on in Figure 1. Here H and V denote dipoles which kick in the Horizontal and Vertical planes respectively. X denotes the superperiod and C and D stand for "Corrector" and "Dipole".)

#### 4 Results

Figure 4 shows the horizontal (red curve) and vertical (blue curve) COD for one of the 101 distributions of quadrupole placement errors. The dipole corrector kicks required to correct the COD are shown in Figure 5.

Figure 6 shows the extreme values (maximum and minimum) of the horizontal (red) and vertical (blue) COD for the entire ensemble of 101 COD's. Here we see extreme values of -17 and +13 mm for the horizontal and vertical COD's respectively. The RMS values for the ensemble of 101 COD's are plotted in Figure 7; note the correlation with the beta functions. Figure 8 shows the extreme values of the horizontal (red) and vertical (blue) kicks required to correct the COD's. Here we see that all kicks are within the range of  $\pm 0.45$  milliradians.

The CODs produced by the displacement of a single quadrupole at a time were also examined. Each of the 13 quadrupoles in a superperiod was displaced in turn by 1 mm in the horizontal and vertical planes. The maximum horizontal and vertical corrector kicks required to correct the CODs are listed in Table 1. All kicks are within the range of  $\pm 0.50$  milliradians.

### 5 Dipole Corrector Strength

The integrated strength of the dipole corrector currently under design is

$$BL = \int B \, dl = 7.421 \times 10^{-3} \, \mathrm{Tm}$$
 (2)

at 13 Amps. For protons with 1 GeV kinetic energy and rigidity  $B\rho = 5.6574$  Tm, this gives a kick of

$$\phi = BL/(B\rho) = 1.31 \text{ milliradians} \tag{3}$$

at 13 Amps, which is more than adequate for correcting the errors considered here.

## References

- C. J. Gardner, "Closed Orbit Distortion and Correction in the Four-Fold Symmetric NSNS Ring", BNL/SNS Tech. Note No. 31, April 17, 1997.
- J. Wei (Editor), "Preliminary Change Request for the SNS 1.3 GeV-Compatible Ring", BNL/SNS Tech. Note No. 76, May 4, 2000.
- [3] J. Milutinovic and A.G. Ruggiero, "Closed Orbit Analysis for the AGS Booster", Booster Tech Note No. 107, February 1, 1988
- [4] B. Autin, "Lattice Perturbations", AIP Conference Proceedings No. 127, American Institute of Physics, (1985) 139-200.



Figure 1: Elements and Layout for One Superperiod of the 248 Meter SNS Accumulator Ring Lattice.



Figure 2: Beta and Dispersion for 1 Superperiod ( $Q_H = 6.3, Q_V = 5.8$ ).



Figure 3: Same for Entire 248 meter Lattice  $(Q_H = 6.3, Q_V = 5.8)$ .



Figure 4: Typical COD due to Quadrupole Displacements.



Figure 5: Dipole Kicks Required to Correct COD.



Figure 6: Maximum and Minimum COD For 101 Error Distributions.



Figure 7: RMS COD for 101 Error Distributions.



Figure 8: Maximum Kicks Required to Correct CODs.

$\Delta x = \Delta y = 1 \text{ mm}$				
Quad	H Dipole	$\phi_H \ (\mathrm{mr})$	V Dipole	$\phi_V (\mathrm{mr})$
QVA1	DHTA2	+0.11	DVTA1	-0.25
QHA2	DHTA2	-0.36	DVTA3	+0.11
QVA3	DHTA2	+0.12	DVTA3	-0.38
QHA4	DHTA4	-0.36	DVTA3	+0.11
QVA5	DHTA6	+0.12	DVTA5	-0.38
QHA6	DHTA6	-0.36	DVTA5	+0.11
QVA7	DHTA6	+0.12	DVTA7	-0.38
QHA8	DHTA8	-0.35	DVTA7	+0.11
QVA9	DHTA8	+0.11	DVTA9	-0.25
QHA10	DHTA10	-0.43	DVTA10	+0.44
QVA11	DHTA10	+0.27	DVTA10	-0.49
QVA12	DHTA13	+0.27	DVTA13	-0.49
QHA13	DHTA13	-0.43	DVTA13	+0.44

 Table 1: Dipole Kicks vs Quad Displacement