



Brookhaven
National Laboratory

BNL-101544-2014-TECH

RHIC/PG/1;BNL-101544-2013-IR

Intrabeam Scattering Computer Calculations And Other Performance Issues

A. G. Ruggiero

November 1983

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No. DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

INTRABEAM SCATTERING COMPUTER CALCULATIONS
AND
OTHER PERFORMANCE ISSUES

A.G. Ruggiero

(BNL, November 17, 1983)

Intrabeam Scattering Computer Calculations

Smooth lattice ($\eta' = \beta' = 0$) $\beta = 30\text{m}$ $\eta = 2.0\text{m}$
 (line #54)

δ , rms relative energy spread

$\epsilon = 2\pi\sigma^2/\beta$, rms betatron emittance

$$\tau_{\beta}^{-1} = \dot{\epsilon}/2\epsilon$$

$$\tau_E^{-1} = \dot{\delta}/\delta \quad (\tau_E^{-1})_{\text{bunched}} = 0.5 \times (\tau_E^{-1})_{\text{unbunched}}$$

I , average current for unbunched beams = $Ne f_{\text{revol}}$
 I , peak current for bunched beams

For bunched beams

$$I = \frac{Ne\beta c}{\sqrt{2\pi}\sigma_e}$$

βc , beam velocity

N , no. of particles in the bunch

σ_e , rms bunch length

Case considered Gold (Au) $A = 197$ $Z = 79$

The numbers in the next two tables are for

$$I = 1\text{mA-particle}$$

Emittances given are normalized

τ_{β}^{-1} is for horizontal plane. The vertical emittance is stable or slightly damped

	ϵ_H	ϵ_V	δ	τ_ϵ^{-1}	τ_β^{-1}		case #
	normalized		10^{-3}	hour ⁻¹	hour ⁻¹		
	$\pi \cdot \text{mm} \cdot \text{mrad}$						
B	0.4	10.	0.04	42.952	2.3208	$\gamma = 12$	13
B			0.12	1.3797	1.8133		15
B			0.4	.0389	0.8406		18
U			0.4	.0778	0.8406		1
B			1.2	.0014	0.3007		2
B	2.0	2.0	0.04	24.3211	0.0812	$\gamma = 12$	17
B			0.1	2.643	0.0553		4
B			0.4	0.0184	0.0061		14
U			0.4	0.0367	0.0061		7
B	4.0	4.0	0.1	1.21	0.0127	$\gamma = 12$	5
U			0.2	0.3767	0.0079		9
U			0.4	0.0347	0.0029		8
U			0.8	0.0004	0.0001		10
B	0.4	10.	0.035	1.2813	0.6290	$\gamma = 100$	16
B			0.35	0.0028	0.1358		3
B	4.0	4.0	0.1	0.0653	0.0262	$\gamma = 100$	6
B			0.2	0.0123	0.0195		11
B			0.4	0.0019	0.0119		12

Eighteen (18) cases have been considered

For each case 100 lattice values (β, η) have been also considered

$\beta = 5$ to 50 , step 5 meters
 $\eta = 0.5$ to 5 , step 0.5 meters

Space Charge Calculation At Injection in the Booster

ϵ_N , normalized emittance

Actual emittance, $\epsilon = 6\pi \sigma^2 / \beta_{lat} = \epsilon_N / (\beta\gamma)$

N_B , total number of particles injected into the Booster

Space charge limit Formula is

$$\frac{N_B}{\epsilon_N} = (\beta\gamma^2) \frac{\pi B_f \Delta\nu}{2\epsilon_0 F} \frac{A}{Q^2} \quad (1)$$

Assumption: "round" beam, that is $\epsilon_H = \epsilon_V$

B_f , bunching factor = 0.5

$\Delta\nu$, betatron-tune depression = 0.1

$\epsilon_0 = 1,535 \times 10^{-18}$ m, classical proton radius

A , atomic mass = 197 for Gold

Q , charge state = 34, partially stripped ions

F , form factor ~ 1 for $\beta \ll 1$ and $\gamma \sim 1$

We take a Booster Acceptance of 40π mm-mrad and we assume we dilute the beam, by steering and multi-turn injection, until this aperture is full and the space charge limit is reached.

The following table explores the effect of the injected kinetic energy (T) on the space charge limit.

Procedure:

- i Assign Kinetic injection energy, T
- ii Calculate relativistic factors β and γ
- iii Calculate phase-space density at the limit N_B/E_N , from (1)
- iv Calculate Normalized Emittance from

$$E_N = (\beta\gamma) (40 \pi \text{ mm.mrad})$$

- v Calculate number of particles N_B that can be injected into the Booster
- vi Assume 3 bunches and a 50% efficiency for full stripping between Booster and AGS
The number of particles/bunch at transfer to the Collider is

$$N = N_B / (2 \times 3)$$

- vii Calculate revolution period $\tau = C/\beta c$
 C , Booster circumference = 201.75 m

- viii Assume a pulse from the Tandem 250 psec and a d.c. current of 4.4 μAmp - particle.
Calculate no. of particles per turn

$$N_B/\text{turn} = (4.4 \mu\text{Amp-particle}) \times \tau$$

- ix Calculate required numbers of turns at injection to get at the total N_B

$$\text{no. of turns} = N_B / (N/\text{turn})$$

- x Calculate required pulse length = (no. of turns) $\times \tau$

T	β	δ	N_B/E_N	E_N	N_B
MeV			$\pi^{-1} m^{-1}$	$\pi mm \cdot mrad$	
1	.04613	1.001066	4×10^{14}	1.85	7.4×10^8
1.5	.05648	1.001599	5×10^{14}	2.26	1.13×10^9
2	.06519	1.002132	5.7×10^{14}	2.61	1.5×10^9
3	.07978	1.003197	7×10^{14}	3.20	2.24×10^9
4	.09204	1.004263	8.1×10^{14}	3.70	3×10^9
5	.10283	1.005329	9.1×10^{14}	4.15	3.74×10^9

T	τ	N	N_B/turn	no. turns	Pulse length
MeV	μsec	$\times 10^8$	$\times 10^8$		μs
1	14.6	1.23	4	1.85	27
1.5	11.9	1.88	3.3	3.4	40.5
2	10.3	2.48	2.83	5.3	54.6
3	8.43	3.73	2.32	9.7	81.8
4	7.3	5.0	2.0	15	109.5
5	6.54	6.24	1.8	21	137

Performance

Long Bunches, High Intensity
Crossing at an Angle

$$L = N_c^2 B f_{rev} / 4\pi \left(\frac{d}{2} \sigma_e\right) \sigma_v$$

B , no. of bunches = 3

N_c , no. of particles / Bunch in colliding mode = 6×10^{10}

f_{rev} , revolution frequency = 78,1973 KHz

d , total crossing angle = 4 mrad

σ_e , rms bunch length = 50 ns

σ_v , rms beam height = 0.037 mm

$$L = 1.8 \times 10^{27} \text{ cm}^{-2} \text{ s}^{-1}$$

Longitudinal stability of the Long Bunches

$$|Z/n| = \frac{E |\eta|}{e I_p} \left(2 \frac{\sigma_E}{E} \right)^2 \frac{A}{Z^2}$$

$$I_p, \text{ peak current} = \frac{N_e \beta_c}{c} / (\sigma_z \sqrt{2\pi})$$

$$N_e, \text{ no. of particles / bunch} = 6 \times 10^{10}$$

$$\sigma_z, \text{ rms bunch length} = 50 \text{ m} \quad (\sigma_z = 0.17 \text{ } \mu\text{sec})$$

$$I_p = 0.023 \text{ Amp-particle} \quad (\beta \approx 1)$$

For Gold (Au) $A = 197$ and $Z = 79$

Assume a coupling impedance of $|Z/n| = 10 \text{ ohms}$

E , energy per nucleon $\approx 100 \text{ GeV/A}$

$$\eta = \gamma^{-2} - \gamma_T^{-2}, \quad \gamma_T = \text{transition energy / rest energy}$$

σ_E/E , rms energy spread at stability (could be larger)

$$B, \text{ bunch area} = 6\pi \sigma_E \cdot \sigma_E$$

Assuming 3 bunches per beam the total area of each beam is

$$3B$$

The following table explores the dependence with γ_T of the threshold spread σ_E/E at 100 GeV/A and the unbunched beam rms spread at 12 GeV/A using the formula

$$3B = 4 T_{\text{total}} \sigma_E, \quad T_{\text{total}} = 12.788 \text{ } \mu\text{sec}$$

δ_T	$ z $	σ_E/E threshold @ 100 GeV/A	B eV/A-sec	σ_E/E unbunched @ 12 GeV/A
10	.0099	.43 $\times 10^{-4}$	13.8	675×10^{-4}
20	.0024	.87	27.9	1.4×10^{-4}
30	1.011×10^{-3}	1.34	42.9	2.0×10^{-4}
50	3×10^{-4}	2.5	80.1	3.9×10^{-4}
80	5.625×10^{-5}	5.7	182.7	8.9×10^{-4}

In the following table, T is the kinetic energy at injection into the Booster, N is the number of ions per bunch at transfer between AGS and Collider.

We assume: there are 3 bunches in the Booster, only these 3 bunches are accelerated in the AGS at the time, so that there are only 3 bunches transferred to the Collider every AGS pulse.

n, number of bunches from the AGS required to get $3 \times 6 \times 10^{10} = 1.8 \times 10^{11}$ ions per beam

The number of AGS pulses are therefore $n/3$

The Collider (each ring) is filled with 19 AGS pulses in a 'box-car' fashion ($h=57$) and n_s RF stacking pulses

The filling time is calculated assuming two minutes for a RF stacking cycle = (1 min AGS + 1 min RF)

T	N	n	no. of AGS pulses	filling sequence	Filling Time
MeV	$\times 10^8$				
1	1.23	1461	487	19 BoxCar * 77 RF stacking	2h 34 min
1.5	1.88	957	319	51	1h 42 min
2	2.48	726	242	39	1h 18 min
3	3.73	483	161	26	52 min
4	5.0	360	120	19	38 min
5	6.24	289	97	16	32 min

The average current at injection ($\gamma \sim 12$) is

$$I = 2.25 \text{ nA - particle}$$

and the peak current at top energy ($\gamma \sim 100$) is also the same

Take $\gamma_1 = 10$

σ_E/E @ 100 GeV/A $.43 \times 10^{-4}$

σ_E/E @ 12 GeV/A $.675 \times 10^{-4}$

E_N	γ	t_E	t_B
π .mm.mrad		hours	hours
2	12	0.03	6.
4.	12.	0.09	20.
2	100.	-	-
4.	100.	1.5	11

Individual Bunch Area at transfer from the AGS to the Collider

$S = 0.014 \text{ eV/A-sec} / 0.072$

having included a 50% dilution factor for transfer, RF stacking and Acceleration.

~~Handwritten scribbles and signatures at the bottom of the page.~~

Take $\gamma_T = 30$

σ_E/E	@	100 GeV/A	1.34×10^{-4}
σ_E/E	@	12 GeV/A	2.0×10^{-4}

E_N	δ	t_E	t_p
mm-sec		hours	hours
2	12	0.5	25
4	12	1.2	56
2	100	-	-
4	100	8	20

Individual Bunch Area at transfer from the AGS to the Collider

$$S = 0.044 \quad / \quad 0.22 \quad \text{eV/A-sec}$$

having included a 50% dilution factor for transfer, RF stacking and acceleration.

~~Individual Bunch Area at transfer from the AGS to the Collider~~

Take $\gamma_T = 50$

σ_E / E @ 100 GeV/A 2.5×10^{-4}

σ_E / E @ 12 GeV/A 3.9×10^{-4}

E_N	γ	t_c	t_p
mm-rad		hours	hours
2	12	12	74
4	12	13	150
2	100	-	-
4	100	6	30

Individual Bunch Area at transfer from the AGS to the Collider

$S = 0.002 / 0.4 \text{ eV/A} \cdot \text{sec}$

having included a 50% dilution factor for transfer, RF stacking and Acceleration

Take

$$\gamma_T = 80$$

σ_E/E @ 100 GeV/A

$$5.7 \times 10^{-4}$$

σ_E/E @ 12 GeV/A

$$8.9 \times 10^{-4}$$

E_N	γ	t_E	t_p
Transmitted		hours	hours
2	12	2100	2100
4	12	1000	4500
2	100	-	-
4	100	200	50

Individual Beam Area at transfer from the AGS to the Collider

$$S = 0.19 / 0.95 \text{ eV/A-sec}$$

having included a 50% dilution factor for transfer, RF stacking and acceleration.

The luminosity of $1.8 \times 10^{27} \text{ cm}^{-2} \text{ s}^{-1}$ can be obtained if

$$\sigma_v = 0.037 \text{ mm}$$

at the interaction region

This corresponds to a $\beta_v^* = 2 \text{ m}$ with a normalized emittance $E_N = 0.4 \pi \cdot \text{mm} \cdot \text{mrad}$

We have now

E_N	β_v^*
0.4 $\pi \cdot \text{mm} \cdot \text{mrad}$	2 m
2.0	0.4 m
4.0	0.2 m

or with $\beta_v^* = 2 \text{ m}$

E_N	L
0.4 $\pi \cdot \text{mm} \cdot \text{mrad}$	$1.8 \times 10^{27} \text{ cm}^{-2} \text{ s}^{-1}$
2.0	0.8
4.0	0.57