



BNL-101573-2014-TECH

RHIC/PG/30;BNL-101573-2013-IR

Parameters Of The RF System For The “Weak-Focusing” Lattices

H. Hahn

January 1984

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No. DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

PARAMETERS OF THE RF SYSTEM
FOR THE "WEAK-FOCUSING" LATTICES

H. HAHN

(BNL January 20, 1984)

rf REQUIREMENTS
(Parabolic Distribution)

Bunch half length $= \sqrt{5} \sigma_L$

Bunch phase half width $\phi = \sqrt{5} \sigma_L h/R$

Bunch half height $\Delta_E = \sqrt{5} \delta_E$

Bunch area/amu $S = 5\pi \sigma_L \delta_E \gamma E_o / c = \frac{\gamma E_o}{2 h f_o} \Delta_E \phi$

In the small-amplitude approximation and stationary

$$\phi = \left(\frac{8\pi |\eta| h^3 f_o^2 A^{1/4}}{\gamma E_o eV Q} \right)^{1/4} \sqrt{S}$$

$$\Delta_E = \frac{2h f_o S}{\gamma E_o \phi}$$

Bucket half height required, stationary

$$\Delta_B = \frac{\Delta_E}{\sin \phi/2}$$

Bucket Area/amu required

$$A_B = \frac{4}{\pi} \frac{\gamma E_o}{h f_o} \Delta_B$$

Voltage required

$$V = \frac{\pi}{2} \frac{h |\eta| \gamma E_o A}{e Q} \Delta_B^2$$

$$V \approx 8\pi \frac{|\eta| h^3 f_o^2 A S^2}{e \gamma E_o Q \phi^4} \quad (\phi \ll \pi)$$

Parameter Variations with h_{rf}
(Equipartition)
 $\gamma = 100, Au$

Lattice	N_B	h_{rf}	δ_E	S eV·sec	L $cm^{-2}sec^{-1}$	Diamond cm rms	V MV
	$\times 10^9$	$\times 57$	$\times 10^{-4}$		$\times 10^{26}$		
			$\alpha = 0 \text{ mrad}$				
15/120°	1	12	11.3	3.8	10.5*	29	2.2
	1	6	9.8	6.6	14.*	57	0.85
12/90°	1	12	6.9	2.3	5.6	29	2.1
	1	6	6.0	4.0	7.4	57	0.81
	1	1	4.2	16.9	15.1*	343	0.066
9/120°	1	6	5.9	4.0	8.4	57	0.95
			$\alpha = 2 \text{ mrad}$				
15/120°	2	12	12.9	4.4	11.	12	3.0
	2	6	11.3	7.6	6.7	14	1.1
	1	6	9.8	6.6	1.9	13	0.85
12/90°	2	12	7.9	2.7	7.6	14	2.8
	2	6	6.9	4.6	4.8	18	1.1
	2	1	4.8	19.4	1.2	17	0.087
	1	6	6.0	4.0	1.4	16	0.81
9/120°	2	6	6.7	4.6	5.1	17	1.2

* $\Delta v > 0.003$
BB

MOMENTUM SPREAD AT TRANSITION

The momentum spread at transition scales like

$$\delta_E \propto \left(\frac{h^2}{\gamma_{tr}^2} \frac{V^2}{\dot{B}} \cos^2 \phi_s \right)^{1/6}$$

with $V \sin \phi_s = 2\pi R \rho \dot{B}$

Assuming the same rf system, the lattices with $\gamma_{tr} \approx 25$ require at transition about 15% more momentum aperture than one with $\gamma_{tr} \approx 38$.

An acceptable rf system for the $\gamma_{tr} \approx 25$ lattices is obtained by using (primed quantities):

$$h' = \frac{1}{2} h; \quad V' = \frac{1}{5} V; \quad \dot{B}' = \frac{1}{4} \dot{B}; \quad \phi'_s \approx \frac{5}{4} \phi_s$$

leading to

$$\delta'_E = 0.7 \delta_E$$

The resulting physical aperture requirement due to momentum spread is

$$(X'_{p \max} = 1.57 \text{ m}, X_{p \max} = 0.7 \text{ m})$$

$$\sigma'_H = 1.57 \sigma_H$$

SUGGESTED rf PARAMETERS

$$f_{\text{rf}} = 6 \times 57 \times f_0 = 26.7 \text{ MHz}$$

$$V_{\text{max}} = 1 \text{ MV}$$

$$V_{\text{acceleration}} = 200 \text{ kV}$$

$$\text{Acceleration time} = 2 \text{ min.}$$

Questions:

- What is dynamics of intrabeam scattering at operating point.
- Parzen will calculate $L = L(t)$
 $\sigma = \sigma_L(t)$
- Slowest beam growth is expected, if full voltage is reached at the end of the acceleration cycle, since

$$\tau_E^{-1} \propto \frac{N_B}{\epsilon S \delta_E^2}; \quad \tau_H^{-1} \propto \frac{N_B}{\epsilon^2 S}$$

CHOICE OF TRANSITION ENERGY

Due to intrabeam scattering the momentum spread of the bunch increases until $\Delta_E = \Delta_B$. If this limit is exceeded, the particles are lost.

At constant voltage

$$\Delta_B^2 \propto \frac{1}{h \gamma |\eta|} = \frac{\gamma_{tr}}{h |\gamma/\gamma_{tr} - \gamma_{tr}/\gamma|}$$

The bucket height requirements vary with energy according to

$$\Delta_E \propto \frac{1}{\sqrt{\gamma}} \quad (\text{equipartition})$$

$$\Delta_E(\gamma=12) > 1.4 \Delta_E(\gamma=100) \quad (\text{Parzen})$$

Equivalent performance over energy range, (i.e. $L \propto \gamma$) requires

$$\gamma_{tr}^2 = \gamma_1 \gamma_2 \frac{(\Delta_1/\Delta_2)^2 \gamma_1 + \gamma_2}{\gamma_1 + (\Delta_1/\Delta_2)^2 \gamma_2}$$

For $\gamma_1=12$ and $\gamma_2=108$ follows the optimized transition energy ($\Delta_1/\Delta_2 \approx 1.4$):

$$\gamma_{tr} = 36 \times 0.6 \approx 22$$