

Injection Kickers as Vertical Pingers

W. MacKay

April 1996

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No. DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Injection Kickers as Vertical Pingers Waldo MacKay

One of the methods of measuring tunes in a hadron storage ring involves inducing a coherent betatron oscillation of one bunch by *pinging* the bunch with a single kick. One or more of the injection kicker modules should provide a sufficient kick for the vertical plane. Coupling through sextupoles may eliminate the necessity for a horizontal pinger.

Each RHIC ring has four injection kicker modules which will provide up to 1.9 mr of vertical bend for a beam whose rigidity is $p/q = 100\text{T}\cdot\text{m}$. Even at stored energies ($p/q = 840\text{T}\cdot\text{m}$) the corresponding kick of 0.23 mr would most likely kick a single bunch out of the ring within one turn. It should be possible to fire the kickers reliably at one quarter of their usual strength. Each module has a separate Blumlein pulser. Although the four pulsers are charged from a single power supply, high voltage switches will allow only selected pulsers to charge, so that just one module may be fired. This factor of 16 in the dynamic range yields kick angles from 0.014 to 0.23 mr at storage energies, and from 0.12 to 1.9 mr at injection.

The effect of a kick θ_k translates into a beam offset given by the formula

$$\delta y(s) = \theta_k \sqrt{\beta_0 \beta(s)} \sin \psi(s),$$

where β_0 is the vertical β -function at the kicker, and $\beta(s)$ and $\psi(s)$ are the respective β -function and phase advance at location s . Table 2 lists β_v and relative phase advances for the injection kicker magnets of the Yellow ring.

Table 1. β_v at Kickers

| Kicker | β_v [m] | ψ [mr] |
|-------------|---------------|-------------|
| yki1 | 38.3 | 0.0 |
| yki2 | 33.1 | 37.3 |
| yki3 | 28.4 | 80.5 |
| yki4 | 24.3 | 130.9 |

Taking kicker **yki4** with the smallest $\beta_0 (= 24.3\text{mr})$, typical maximum deflections around the ring are shown in Table 2 for the extreme values of pings at injection and storage. The $\beta_{\text{max}} = 50$ m occurs in the arcs, whereas the other values 150, and 1500 m occur in the triplets for $\beta^* = 10$ m and $\beta^* = 1$ m, respectively.

Table 2. Maximum Offsets

| | Injection | | Storage | |
|----------------------|--------------------------------------|-------------------------------------|---------------------------------------|--------------------------------------|
| β_{max} | $\delta y(\theta_k = 0.12\text{mr})$ | $\delta y(\theta_k = 1.9\text{mr})$ | $\delta y(\theta_k = 0.014\text{mr})$ | $\delta y(\theta_k = 0.23\text{mr})$ |
| 50 m | 4 mm | 66 mm | 0.5 mm | 8 mm |
| 150 m | 7 mm | 115 mm | 0.9 mm | 14 mm |
| 1500 m | [†] 23 mm | [†] 360 mm | 2.7 mm | 44 mm |

[†] $\beta^* = 1$ m is not used at injection.

For stored beam, a single kicker module will probably work quite well. Pinging the beam at injection may be unnecessary, since we can detune the injection damper.