

RHIC Aperture Requirements

H. Hahn

March 1984

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No. DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

RHIC APERTURE REQUIREMENTS

H. Hahn

Brookhaven National Laboratory

March 9, 1984

APERTURE REQUIREMENTS (Au)

γ	$N_B = 1.2 \times 10^9$				0.6×10^9		
	ϵ/π	δ	S (eV.sec)	σ_L (m)	ϵ/π	δ	S (eV.sec)
	$\times 10^{-6}$	$\times 10^{-3}$			$\times 10^{-6}$	$\times 10^{-3}$	
5	70	1.0			49	0.93	
12.5 operation	34.5	1.22		1.25	25	1.03	
12.5 injection	10	0.53	0.2		10	0.53	0.2
26.4 transition	10	4.2 *	1.0				
100	18.4	0.79		1.15	15	0.59	

* LMV, $h = 6 \times 57$, 30 sec acceleration time

Physical aperture requirements (operation at $\gamma = 12.5$)

$$= \pm \sqrt{6} \left(X_p \delta + \sqrt{\frac{\epsilon \beta}{\pi \gamma}} \right)$$

$$= \pm \left(x_{c.o. @ \Delta p/p = \pm 3 \times 10^{-3}} + \sqrt{6} \frac{\epsilon \beta}{\pi \gamma} \right) \quad (\text{J. Claus})$$

Good field aperture requirement

$$= \pm \left(\sqrt{6} X_p \delta + \sqrt{\frac{\epsilon \beta}{\pi \gamma}} \right)$$

Other aperture requirement definitions

$$\pm 6 \left((X_p \delta)^2 + \frac{\epsilon \beta}{6\pi\gamma} \right)^{1/2} \quad (\text{A. Ruggiero})$$

$$\pm \left(2.64 (X_p \delta + \sqrt{\frac{\epsilon \beta}{6\pi\gamma}}) + 1.2 \text{ cm} \right) \quad (\text{HERA-p})$$

$$\pm \left(8.4 \left((X_p \delta)^2 + \frac{\epsilon \beta}{6\pi\gamma} \right)^{1/2} + 1.2 \text{ cm} \right) \quad (\text{HERA-e})$$

RHIC MAGNET APERTURES
for Luminosity Calculations
(mm)

	Good field		Aperture	
	Arc	Arc	Arc	Low β Insertion
RHIC-3 in	± 25.4	± 32	± 70	
SSC	± 20	± 27	± 27	

Required* - Au				
@ 12.5 operation	± 18	± 36	± 104 vert.	± 86 horiz.
@ 12.5 injection	± 8	± 18	± 56	
@ transition	± 19	± 25	± 39	
@ 100 operation	± 6	± 10	± 27	

*RHIC-2 lattice