

Lattice Alternative For RHIC

M. Puglisi

January 1984

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No. DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

LATTICE ALTERNATIVES FOR RHIC

H. HAHN

(BNL, January 10, 1984)

ASSUMPTIONS

EQUAL IBS DIFFUSION RATES

$$\chi_H^{-1} = \chi_E^{-1} = 0.5 \text{ h}^{-1} (= \chi_V^{-1})$$

$$\chi_L^{-1} \approx 1 \text{ h}^{-1}$$

BEAM-BEAM TUNE SHIFT

$$\Delta\nu_{BB} = 3 \times 10^{-3}$$

BUNCHED BEAM OPERATION

$$h_B = 57$$

$$\sigma_L = 1 \text{ m}$$

EXISTENCE OF BOOSTER

NO MOMENTUM STACKING

BUT DESIGN OF COLLIDER
ALLOWS FOR FUTURE
INJECTOR IMPROVEMENTS

$$N_B \geq 1 \times 10^9 \text{ ions/bunch}$$

ONLY Au-IONS STUDIED

DEFINITIONS

rms beam radius	$\sigma_{H,V} = \left(\frac{\beta_{H,V} \epsilon}{6\gamma \pi} \right)^{1/2}$
beam size maximum in arc	$= 2\sqrt{6} (\sigma_H + \chi_p \delta_E)$
rms diamond length	$\sigma_{\text{diam}} = \frac{\sigma_H \sigma_L}{2\sigma_H + \frac{1}{2} \alpha \sigma_L}$
rms bunch length	$= \sigma_L$
bunch area	$A_B = 6\pi \sigma_L \delta_E \gamma E_0 / c$

LATTICE

ψ = phase shift/cell

L_{HC} = length of half cell

θ_{HC} = deflection/half cell

N_{CS} = number of cells/sextant

$$\langle \beta \rangle = \frac{2 L_{HC}}{\sin \psi}$$

$$\beta_{max} = \langle \beta \rangle \left(1 + \sin \frac{1}{2} \psi \right)$$

$$\langle X_p \rangle = L_{HC} \theta_{HC} \frac{1}{\sin^2 \frac{1}{2} \psi}$$

$$\gamma_{tr} = \frac{\langle \beta \rangle}{\langle X_p \rangle} \cos \frac{1}{2} \psi \quad (\times 1.37 \quad)$$

$$X_{p \max} = \langle X_p \rangle \left(1 + \frac{1}{2} \sin \frac{1}{2} \psi \right)$$

$$\theta_{HC} = \frac{\pi}{6 N_{CS}}$$

$$\int_{HC} B \, d\ell = \frac{388}{N_{CS}} \text{ Tesla} \cdot \text{meter}$$

$$\int_{quad} G \, d\ell = 9.61 N_{CS} \sin \frac{1}{2} \psi \text{ Tesla}$$

LUMINOSITY

$$L = \frac{f_0}{4\pi} h_B N_B^2 \frac{1}{\sigma_V^* \sigma_{\text{Heff}}}$$

$$f_0 = \frac{c}{2\pi R}$$

$$\sigma_{\text{Heff}} = (\sigma_H^{*2} + (\frac{1}{2} \alpha \sigma_L)^2)^{1/2}$$

BEAM-BEAM TUNE SHIFT ($\Delta\nu_{\text{BB}} < 3 \times 10^{-3}$)

$$\Delta\nu_{\text{BB}} = \frac{r_p}{2\pi} \frac{Q^2}{A} \frac{N_B}{\gamma} \frac{\beta_V^*}{\sigma_V (\sigma_V + \sigma_{\text{Heff}})}$$

TOLERABLE COUPLING IMPEDANCE

$$\frac{Z}{n} = 4 \frac{A}{Q^2} \frac{\gamma E_0}{e I_p} |n| \delta_E^2$$

$$n = \gamma^{-2} - \gamma_{\text{tr}}^{-2}$$

$$I_p = \frac{c}{\sqrt{2\pi}} \frac{N_B}{\sigma_L}$$

INTRA BEAM SCATTERING
(Courant, Bjorken & Mtingwa)

Diffusion rate ($\gamma \gg \gamma_{tr}$)

$$\tau^{-1} = \tau_H^{-1} + \tau_V^{-1} + \tau_E^{-1}$$

$$\tau_V^{-1} \approx 0$$

$$\tau_E^{-1} = \left(\frac{\sigma_H}{\langle X_p \rangle \delta_E} \right)^2 \tau_H^{-1}$$

$$\tau_H^{-1} = \frac{9}{4} L_g r_p^2 c \left(\frac{Q^2}{A} \right)^2 \frac{N_B}{\sigma_L} \frac{1}{\gamma \delta_E} \frac{\pi^2}{\epsilon_H \epsilon_V} \frac{\langle X_p \rangle}{\langle \beta \rangle} \left[1 + \left(\frac{\sigma_H}{\langle X_p \rangle \delta_E} \right)^2 \right]^{-1/2}$$

$$-\frac{1}{L} \frac{dL}{dt} = \tau_V^{-1} + \frac{\sigma_H}{\sigma_{Heff}} \tau_H^{-1} + \frac{1}{2} \alpha \frac{\sigma_L}{\sigma_{Heff}} \tau_E^{-1}$$

with $L_g \approx 20$

$$r_p = 1.5347 \times 10^{-18} \text{ m}$$

N_B = number of ions/bunch

σ_L = bunch length

EQUIPARTITION

$$\tau_E = \tau_H$$

$$\delta_E = \frac{\sigma_H}{\langle X_p \rangle}$$

GOAL: $\tau_H = \tau_E = 2 \text{ hours}$

DESIGN CONSTRAINTS: $\epsilon = \epsilon_H = \epsilon_V \propto (\tau_H \dots)^{1/2 \cdot 5}$

$$\delta_E \propto (\tau_H \dots)^{1/5}$$

H. Hahn

1/9/84

LATTICE ALTERNATIVES

Lattice	L_{HC} (m)	$\langle X_p \rangle$ (m)	X_p max (m)	$\langle \beta \rangle$ (m)	β_{max} (m)	γ_{tr}	f_{HC} B d1 (Txm)	f_{quad} G d1 (T)
9/90°	19.8	2.05	2.77	39.5	67.5	19	2x4.94x4.36	61.2
9/105°	19.8	1.63	2.27	40.9	73.4	21	2x4.94x4.36	68.7
9/120°	19.8	1.37	1.96	45.6	85.2	23	2x4.94x4.36	74.9
12/90°	14.8	1.15	1.56	29.7	50.6	25	2x3.3 x4.9	81.6
15/120°	11.9	0.49	0.70	27.4	51.1	38	3.3 x7.83	124.9

NO CELLS/SEXTANT= 9 PHI/CELL= 00.0 SIGMA= 1.0
 L/HCELL= 19.76 ML= 41.42 QL= 54.87
 XP= 2.05 XPMAX= 2.77 HETA= 39.53 BETAMAX= 07.49 BETA*V= 3.0 BETA*H= 3.0
 GAMMATP= 19.3
 GAMMA= 100.0 A= 197.0 n= 79.0
 HR= 57.0

ALPHA	PART/BUNCH	EMITTANCE/PI	DELTA F RMS	FV.SEC/RUNCH	LUMINOSITY	NU SHFT	DIAM RMS	BEAM SIZE	Z/N
0.	1.00E+09	1.35E-05	4.61E-04	2.72E+00	5.25E+26	1.72E-03	5.00E-01	1.23E-02	3.4E+02
0.	2.00E+09	1.78E-05	5.29E-04	3.12E+00	1.59E+27	2.60E-03	5.00E-01	1.41E-02	2.2E+02
0.	3.00E+09	2.10E-05	5.74E-04	3.38E+00	3.04E+27	3.32E-03	5.00E-01	1.53E-02	1.8E+02
0.	4.00E+09	2.35E-05	6.08E-04	3.59E+00	4.82E+27	3.94E-03	5.00E-01	1.62E-02	1.5E+02
0.	5.00E+09	2.57E-05	6.35E-04	3.75E+00	6.89E+27	4.51E-03	5.00E-01	1.70E-02	1.3E+02
0.	6.00E+09	2.77E-05	6.59E-04	3.89E+00	9.22E+27	5.03E-03	5.00E-01	1.76E-02	1.2E+02
0.	7.00E+09	2.94E-05	6.80E-04	4.01E+00	1.18E+28	5.52E-03	5.00E-01	1.82E-02	1.1E+02
0.	8.00E+09	3.11E-05	6.98E-04	4.12E+00	1.46E+28	5.98E-03	5.00E-01	1.86E-02	9.7E+01
0.	9.00E+09	3.26E-05	7.15E-04	4.22E+00	1.76E+28	6.42E-03	5.00E-01	1.91E-02	9.1E+01
2.00E-02	1.00E+09	1.35E-05	4.61E-04	2.72E+00	1.42E+26	6.90E-04	1.71E-01	1.23E-02	3.4E+02
2.00E-03	2.00E+09	1.78E-05	5.29E-04	3.12E+00	4.55E+26	1.16E-03	1.87E-01	1.41E-02	2.2E+02
2.00E-03	3.00E+09	2.10E-05	5.74E-04	3.38E+00	9.38E+26	1.54E-03	1.97E-01	1.53E-02	1.8E+02
2.00E-03	4.00E+09	2.35E-05	6.08E-04	3.59E+00	1.56E+27	1.93E-03	2.03E-01	1.62E-02	1.5E+02
2.00E-03	5.00E+09	2.57E-05	6.35E-04	3.75E+00	2.33E+27	2.28E-03	2.09E-01	1.70E-02	1.3E+02
2.00E-03	6.00E+09	2.77E-05	6.59E-04	3.89E+00	3.22E+27	2.60E-03	2.13E-01	1.76E-02	1.2E+02
2.00E-03	7.00E+09	2.94E-05	6.80E-04	4.01E+00	4.23E+27	2.91E-03	2.17E-01	1.82E-02	1.1E+02
2.00E-03	8.00E+09	3.11E-05	6.98E-04	4.12E+00	5.36E+27	3.21E-03	2.20E-01	1.86E-02	9.7E+01
2.00E-03	9.00E+09	3.26E-05	7.15E-04	4.22E+00	6.60E+27	3.49E-03	2.23E-01	1.91E-02	9.1E+01
1.00E-02	1.00E+09	1.35E-05	4.61E-04	2.72E+00	2.72E+25	1.70E-04	4.71E-02	1.23E-02	3.4E+02
1.00E-02	2.00E+09	1.78E-05	5.29E-04	3.12E+00	9.48E+25	2.93E-04	5.34E-02	1.41E-02	2.2E+02
1.00E-02	3.00E+09	2.10E-05	5.74E-04	3.38E+00	1.97E+26	4.03E-04	5.73E-02	1.53E-02	1.8E+02
1.00E-02	4.00E+09	2.35E-05	6.08E-04	3.59E+00	3.30E+26	5.05E-04	6.03E-02	1.62E-02	1.5E+02
1.00E-02	5.00E+09	2.57E-05	6.35E-04	3.75E+00	4.93E+26	6.02E-04	6.27E-02	1.70E-02	1.3E+02
1.00E-02	6.00E+09	2.77E-05	6.59E-04	3.89E+00	6.85E+26	6.95E-04	6.48E-02	1.76E-02	1.2E+02
1.00E-02	7.00E+09	2.94E-05	6.80E-04	4.01E+00	9.03E+26	7.85E-04	6.65E-02	1.82E-02	1.1E+02
1.00E-02	8.00E+09	3.11E-05	6.98E-04	4.12E+00	1.15E+27	8.71E-04	6.81E-02	1.86E-02	9.7E+01
1.00E-02	9.00E+09	3.26E-05	7.15E-04	4.22E+00	1.42E+27	9.55E-04	6.95E-02	1.91E-02	9.1E+01

RHIC PERFORMANCE ESTIMATES - Au

$$\begin{aligned}
 N_B &= 1 \times 10^9 \\
 \beta_V^* &= \beta_H^* = 3 \text{ m} \\
 \alpha &= 0 \\
 \sigma_L &= 1 \text{ m} \\
 h_B &= 57
 \end{aligned}$$

Lattice	ϵ/π (m)	δ_E	H-size (cm)	L ($\text{cm}^{-2}\text{sec}^{-1}$)	Δv_{BB}
	$\times 10^{-6}$	$\times 10^{-3}$		$\times 10^{26}$	$\times 10^{-3}$
		$\gamma = 100$			
9/90°	13.5	0.46	1.23	5.25	1.72
9/105°	11.0	0.53	1.16	6.44	2.11
9/120°	9.0	0.60	1.13	7.91	2.59
12/90°	10.1	0.61	0.92	7.00	2.29
15/120°	5.4	1.0	0.68	13.2	4.32
		$\gamma = 10$ (to be verified)			
9/90°	21.4	1.83	4.90	0.33	1.08
9/105°	17.5	2.12	4.62	0.41	1.33
9/120°	14.2	2.41	4.51	0.50	1.63
12/90°	16.1	2.44	3.67	0.44	1.44
15/120°	8.5	4.01	2.71	0.83	2.72

RHIC PERFORMANCE POTENTIAL - Au

$$\begin{aligned} \gamma &= 100 ; \quad \Delta v_{BB}^* = 3 \times 10^{-3} \\ \beta_V^* &= 2 \quad \beta_H^* = 4.5 \text{ m} \\ \sigma_L &= 1 \text{ m} \quad h_B = 57 \end{aligned}$$

Lattice	α	N_B	ϵ/π (m)	δ_E	L ($\text{cm}^{-2}\text{sec}^{-1}$)	Diamond (cm rms)
	$\times 10^{-3}$	$\times 10^9$	$\times 10^{-6}$	$\times 10^{-3}$	$\times 10^{27}$	
9/90°	0	3.7	22.8	0.60	4.26	50
	2	9.3	33.0	0.72	8.28	24.9
9/105°	0	2.6	16.1	0.65	2.97	50
	2	7.7	24.9	0.80	6.70	23.2
9/120°	0	1.9	11.6	0.69	2.21	50
	2	6.4	18.8	0.88	5.43	21.5
12/90°	0	2.3	14.1	0.73	2.65	50
	2	7.1	22.2	0.91	6.08	22.5
15/120°	0	0.8	4.9	0.96	0.92	50
	2	4.2	9.6	1.34	3.39	17.4

CONCLUSIONS

- ACCURACY MAY BE QUESTIONABLE BUT TREND IS CORRECT
- "WEAK" FOCUSING - LARGE APERTURE HIGHEST LUMINOSITY POTENTIAL REQUIRES BETTER INJECTOR
- STUDY & COST IN MORE DETAIL 2 OPTIMUM-COMPROMISE LATTICES ($\delta_{40} \approx 30$)

9/120° CBA MAGNETS

12/90° NEW MAGNET 3.3 T
~ 3 in. coil id. (bent)
~ 3 1/2 in. coil id. (straight)

- INJECTOR DESIGN

$$N_B = 2 \times 10^9 \text{ (Au)}$$

BOOSTER ENERGY ?