

# Dynamic Aperture Effects Due to Linear Coupling

G. Parzen

May 1991

Collider Accelerator Department  
**Brookhaven National Laboratory**

**U.S. Department of Energy**

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No. DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

## **DISCLAIMER**

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

BNL-45519  
AD/RHIC-94  
Conference Paper

## Dynamic Aperture Effects Due to Linear Coupling

G. Parzen

May 1991

R H I C   P R O J E C T

Brookhaven National Laboratory  
Associated Universities, Inc.  
Upton, NY 11973

Under Contract No. DE-AC02-76CH00016 with the  
UNITED STATES DEPARTMENT OF ENERGY

# DYNAMIC APERTURE EFFECTS DUE TO LINEAR COUPLING\*

G. Parzen

Brookhaven National Laboratory  
Upton, NY 11973, USA

## I. INTRODUCTION

The coupling introduced by the random  $a_1$  can produce considerable distortion of the betatron motion. For a given initial  $x_o, x'_o, y_o, y'_o$ , the maximum  $x$  and the maximum  $y$  for the subsequent motion can be considerably larger when coupling is present. The maximum  $x$  and  $y$  can be used as a measure of the betatron distortion. One effect of this betatron distortion shows up in the dynamic aperture, in a loss in the stability limit,  $A_{SL}$ , found by tracking. The betatron distortion causes the particle to move further out in the magnets, where it sees stronger non-linear fields. Previous tracking[1,2] showed a loss in  $A_{SL}$  due to random  $a_1$  and  $b_1$ . It was noticed then that the loss in  $A_{SL}$  was associated with a betatron motion distortion which was primarily a linear effect. For a given initial  $x, x', y, y'$  the  $x_{max}$  and  $y_{max}$  in the high- $\beta$  magnets were considerably larger (about 30% larger) for those random  $a_1$  distributions which produced the smaller  $A_{SL}$ . The studies described below show that the stability limit,  $A_{SL}$ , depends on the starting location around the ring. This variation in  $A_{SL}$  around the ring can be correlated with the variation in the betatron distortion for particles starting at different places around the ring. It is proposed that the average of the  $A_{SL}$  found by starting at each of the QF, the focusing quadrupoles in the arcs, can be taken as a measure of the dynamic aperture. It is found that the average  $A_{SL}$  is reduced by about 15% by the random  $a_1$  multipoles expected in RHIC.

Computing the stability limit  $A_{SL}$  is made more difficult by the dependence of  $A_{SL}$  on the starting location around the ring. In order to avoid having to compute  $A_{SL}$  for all possible starting locations at a QF, one can make use of an observed correlation between  $A_{SL}$  and a linear parameter, CDF, which is called the coupling distortion function, and which is defined below. Roughly, the CDF is a measure of how large  $x$  or  $y$  may become because of the presence of coupling for a given set of starting conditions  $x_o, x'_o, y_o, y'_o$ . The CDF being a linear parameter can be computed quickly starting at each QF in the ring. The QF with the largest CDF is found to have the smallest  $A_{SL}$ , and the smallest CDF corresponds to the largest  $A_{SL}$ . After finding the QF with the maximum and minimum CDF, one can compute the  $A_{SL}$  for these two starting locations with tracking runs. It is proposed that

the average  $A_{SL}$  around the ring be approximated by taking the average of these two values of  $A_{SL}$  found at the locations where the CDF has its maximum and minimum.

## II. CORRELATION OF CDF AND $A_{SL}$

The coupling distortion function, CDF, is defined by

$$\text{CDF} = \frac{x_{max}(s)}{x_{max,nc}(s)} \quad (1)$$

for a given initial  $x, x', y, y'$  starting at  $s = s_o$ , and in the absence of non-linear fields.  $x_{max,nc}$  is the  $x_{max}$  in the absence of coupling. A similar CDF exists also for the  $y$ -motion. The CDF depends on  $s$  and also on the starting conditions of  $x, x', y, y'$ . Since we are interested in the correlation between the CDF and the  $A_{SL}$  found in tracking studies, we will compute the CDF for the starting conditions  $x' = y' = 0, \epsilon_x = \epsilon_y$ , and at the  $s$  which corresponds to the location of the high- $\beta$  quadrupoles in the insertions.

To compute CDF, one has to compute  $x_{max}(s)$  in the presence of coupling. An analytical result was found for  $x_{max}(s)$  for a given starting  $x, x', y, y'$ . This result is given in Section III.

Table 1: CDF at High  $\beta$  Quads for a particle starting at the focusing quadrupole at the middle of the first arc in RHIC for the RHIC  $\beta^* = 2$  Lattice.

Field Error No.	CDF	$\beta_1$ (m)	$\beta_2$ (m)	$A_{SL}$ (mm)
1	1.32	695	684	8.5
2	1.46	650	644	6.5
3	1.30	682	744	8.5
4	1.55	723	797	7.5
5	1.10	766	752	8.5
6	1.38	625	654	8.5
7	2.10	956	970	4.5
8	1.63	816	764	6.5
9	1.30	687	655	8.5
10	1.35	797	670	7.5

Table 1 lists the coupling distortion function, CDF, and the  $\beta$ -functions of the normal modes,  $\beta_1$  and  $\beta_2$  for ten different distributions of the random field errors expected in RHIC.<sup>3</sup> The CDF is the largest CDF found at any of the high  $\beta$  quadrupoles in the insertions for

\*Work performed under the auspices of the U.S. Department of Energy.

**Table 2:** The coupling distortion function, CDF, starting at different QF for a RHIC lattice with  $\beta^* = 6$  and for  $a_1$  errors corresponding to Seed 8.

QF Element No.	CDF	QF Element No.	CDF
1	1.86	113	1.67
15	1.48	127	1.67
29	1.81	141	1.62
43	1.52	145	1.67
57	1.81	169	1.62
71	1.57	1299	1.28
85	1.71	1313	2.00
99	1.62		

**Table 3:** The coupling distortion function, CDF, and the  $A_{SL}$  found starting at different Q for a RHIC lattice with  $\beta^* = 6$  and Seed 8  $a_1$  errors.

QF Element No.	CDF	$A_{SL}$ (mm)
1313	2.00	10.5
1	1.86	11.5
85	1.71	12.5
15	1.48	13.5
1299	1.28	14.5

either  $x$  or  $y$  motion for a particle starting at the focusing quadrupole in the middle of the first arc in RHIC. The  $\beta_1, \beta_2$  are the largest  $\beta$ -functions of the normal modes found around the accelerator. For  $a_1 = b_1 = 0$ , the largest  $\beta$  functions are  $\beta = 220$  m for  $\beta^* = 6$  and  $\beta^* = 630$  for  $\beta^* = 2$ . A CDF as large as CDF = 2.1 is found for one field error distribution. A simple picture of coupling would suggest CDF  $\simeq 1.4$  resulting from a complete exchange of the emittance between the  $x$  and  $y$  motions. The betatron distortion is about 40% larger for the worst case than what one would expect from the simple picture of a complete exchange of the emittances.

There is some correlation between CDF and  $\beta_1$  and  $\beta_2$ . However, the CDF depends not only on  $\beta_1, \beta_2$  but also on the mismatch in the emittances. For the given initial  $\epsilon_x, \epsilon_y$ , the corresponding  $\epsilon_1, \epsilon_2$  may be larger than  $\epsilon_x, \epsilon_y$  where  $\epsilon_1, \epsilon_2$  are the emittances for the normal modes.

Table 1 also shows the correlation between the CDF and the dynamic aperture which is measured by  $A_{SL}$ .  $A_{SL}$  is found from tracking studies with the random field errors, including higher multipoles, present.  $A_{SL}$  is the largest stable initial  $x$  with the starting conditions  $\epsilon_x = \epsilon_y, x' = y' = 0$ , and starting at the focusing quadrupole at the middle of the first arc in RHIC.

The correlation between the coupling distortion function, CDF, and the dynamic aperture  $A_{SL}$  is good. Note that the  $A_{SL}$  are computed after the coupling has been corrected[3] using the  $a_1$  correctors in the insertions.

In the absence of the random  $a_1, b_1$ , the stability limit has been found to be  $A_{SL} = 7.5$  mm for  $\beta^* = 2$ . The results in Table 1 indicate that for this particular starting place around the ring,  $A_{SL}$  has been reduced to  $A_{SL} = 4.5$  mm for  $\beta^* = 2$  mm.

The above result for  $A_{SL}$  is misleading. It was found at a QF where the coupling distortion function, CDF, has a large value. If the tracking study to find  $A_{SL}$  is done starting on a different QF, a different value of  $A_{SL}$  will be found which is inversely correlated with the CDF at that QF.

If the particle is started at different QF, the value of CDF and  $A_{SL}$  will change at each QF. Table 2 shows this variation in CDF at 14 different QF. The CDF listed is the largest CDF found at high- $\beta$  quadrupoles in the insertions, when the particle is started at different QF.

$A_{SL}$  will also vary around the ring, since  $A_{SL}$  and CDF are correlated. In Table 3  $A_{SL}$  and CDF are listed for a particle starting at 5 different QF in the ring. These 5 points include the largest and smallest CDF found in the ring.  $A_{SL}$  is computed at the QF at which the particle is started.

Since  $A_{SL}$  now depends on which QF the particle is started at, one has the problem of which value of  $A_{SL}$  is to be used for the dynamic aperture. The procedure proposed here is to use the average  $A_{SL}$  found from the  $A_{SL}$  computed at all the QF in the ring.

To compute  $A_{SL,av}$  the average  $A_{SL}$ , one should in principle compute  $A_{SL}$  at all the QF in the ring and then compute the average  $A_{SL}$ . This would require a good deal of effort. Instead, the following procedure was used. The coupling distortion function at the high  $\beta$  quadrupole is computed starting at each QF in the ring. One then locates the QF that give the largest and smallest CDF, CDF<sub>max</sub> and CDF<sub>min</sub>. The stability limit  $A_{SL}$  is computed starting at these two QF. It is assumed that this gives the largest and smallest  $A_{SL}, A_{SL,max}$  and  $A_{SL,min}$ . The average  $A_{SL}$  is then computed as

$$A_{SL,av} = \frac{1}{2} (A_{SL,max} + A_{SL,min})$$

The computation of  $A_{SL,av}$  for the two worst field errors, errors 7 and 8, are shown in Table 4 for two RHIC lattices having  $\beta^* = 6$  and  $\beta^* = 2$ .

The loss in  $A_{SL}$  is now 15%.  $A_{SL}$  has been decreased from 15.5 mm to 13 mm, for  $\beta^* = 6$  from 7.5 mm to 6.5 mm for  $\beta^* = 2$ .

**Table 4:** Computation of  $A_{SL,av}$ .

$\beta^*$	Error No.	$A_{SL}$ max	$A_{SL}$ min	$A_{SL}$ av	CDF Max	CDF Min
6	7	14.5	11.5	13	1.67	1.29
6	8	16.5	10.5	13.5	2.0	1.24
2	7	8.5	4.5	6.5	2.1	1.10
2	8	8.5	6.5	7	1.8	1.21

### III. ANALYTICAL RESULTS FOR $X_{max}$ and $Y_{max}$

In this section, analytical results are given for the maximum  $x$  and  $y$ ,  $x_{max}$  and  $y_{max}$ , that will be reached for a particle with a given initial  $x, x', y, y'$  in the presence of coupling. These results are needed in order to compute the coupling distortion function, CDF. Derivations of these results will be given in a future paper.

Edwards and Teng showed how to transfer to a new set of coordinates  $v, v', u, u'$  which are uncoupled.[5] These new normal coordinates are related to  $x, x', y, y'$  by a  $4 \times 4$  matrix  $R$

$$x = R v .$$

The normal coordinates have emittances  $\epsilon_1$  and  $\epsilon_2$  and  $\beta$ -functions  $\beta_1$  and  $\beta_2$ .  $\epsilon_1$  and  $\epsilon_2$  are invariants. The  $x$  and  $y$  motion can be written as the sum of these two normal modes.

$\beta_1$  and  $\beta_2$  and the  $R$  matrix can be computed from the one turn transfer matrix.[5] For RHIC,  $\beta_1$  and  $\beta_2$  can be considerably larger than  $\beta_x, \beta_y$  by as much as 100% in the worse case found. However, the  $x_{max}, y_{max}$  for a given initial  $x, x', y, y'$  are not simply related to  $\beta_1, \beta_2$ .

For a given set of initial  $x, x', y, y', x_{max}$  and  $y_{max}$  are given by

$$\begin{aligned} x_{max} &= (\beta_1 \epsilon_1)^{\frac{1}{2}} \cos \phi + (\beta_{x,2} \epsilon_x)^{\frac{1}{2}} \sin \phi, \\ \beta_{x,2} &= \overline{D}_{11}^2 \beta_2 + \overline{D}_{12}^2 \gamma_2 + 2 \overline{D}_{11} \overline{D}_{12} \alpha_2, \\ y_{max} &= (\beta_2 \epsilon_2)^{\frac{1}{2}} \cos \phi + (\beta_{y,1} \epsilon_1)^{\frac{1}{2}} \sin \phi, \\ \beta_{y,1} &= D_{11}^2 \beta_1 + D_{12}^2 \gamma_1 + 2 D_{11} D_{12} \alpha_1 . \end{aligned} \quad (2)$$

$D$  and  $\overline{D}$  are  $2 \times 2$  matrices, which together with  $\phi$  define the  $4 \times 4$   $R$  matrix  $R$  is given by

$$R = \begin{pmatrix} I \cos \phi & D \sin \phi \\ -\overline{D} \sin \phi & I \cos \phi \end{pmatrix} \quad (3)$$

$\overline{D} = D^{-1}$ ,  $|D| = 1$  and  $I$  is the  $2 \times 2$  identity matrix.

$\beta_1, \alpha_1, \gamma_1$  and  $\beta_2, \alpha_2, \gamma_2$  are the orbit parameters of the normal modes,  $\epsilon_1$  and  $\epsilon_2$  are the emittances of the normal modes that correspond to the initial  $x, x', y, y'$ .

One can also find expressions for  $x'_{max}$  and  $y'_{max}$ . These are given by

$$\begin{aligned} x'_{max} &= (\gamma_1 \epsilon_1)^{\frac{1}{2}} \cos \phi + (\gamma_{x,2} \epsilon_2)^{\frac{1}{2}} \sin \phi, \\ \gamma_{x,2} &= \overline{D}_{21}^2 \beta_2 + \overline{D}_{22}^2 \gamma_2 + 2 \overline{D}_{21} \overline{D}_{22} \alpha_2, \\ y'_{max} &= (\gamma_2 \epsilon_2)^{\frac{1}{2}} \cos \phi + (\gamma_{y,1} \epsilon_1)^{\frac{1}{2}} \sin \phi, \\ \gamma_{y,1} &= D_{21}^2 \beta_1 + D_{22}^2 \gamma_1 + 2 D_{21} D_{22} \alpha_1 . \end{aligned} \quad (4)$$

Edwards and Teng[5] describe how to compute the  $R$  matrix and  $\beta_1, \alpha_1, \gamma_1$  and  $\beta_2, \alpha_2, \gamma_2$  from the one turn transfer matrix. This then allows one to compute  $\epsilon_1$  and  $\epsilon_2$  from the initial  $x, x', y, y'$ . Equation (2) can then be used to compute  $x_{max}$  and  $y_{max}$  for the given initial  $x, x', y, y'$ , which is needed to compute the coupling distortion function, CDF (see Eq. (1)).

### IV. REFERENCES

- [1] G. Parzen, AD/RHIC-AP-80 (1989).
- [2] G. Parzen, AD/RHIC-72 (1990).
- [3] G. Parzen, AD/RHIC-AP-72 (1988).
- [4] G. Parzen, AD/RHIC-82 (1990).
- [5] D. Edwards and L. Teng, IEEE 1973 PAC, p. 885.