

Definition of a_1 Corrections

H. Hahn

May 1990

Collider Accelerator Department
Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No. DE-AC02-76CH00016 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

RHIC PROJECT
Brookhaven National Laboratory

Definition of a_1 Correctors

H. Hahn & G. Parzen



May 1990

Q₁ CORRECTORS IN ARC

INNER ARCS

Q₉ is focussing

Each QD has $q_1 = 12 \times 1.5 T$, 8 cm



"Vert. Disp"
"Q₉"


a_1 in OUTER ARCS

Q9 are DE Focussing

q at QD : $12 \times 1.5T$; f_{ch}

* NO q_1 at q_9 in 6, 10, 2 o'clock

Note, corrector package at
Q9 in 6, 10, 2 o'clock
has only a_0 (horiz. Dipole)



DAY-ONE

EACH RING :

1 Power supply for 6 sections
"Coupling" only

a_1 at Q2

EACH RING : $12 \times 1.5T$; 13 cm




Fig. IV.2-1. Layout of the Collider.

DAY-ONE POWER SUPPLIES EACH RING :

1 FAMILY 2, 6⁶⁸, 10 o'clock

1 " 4, 8, 12 "

a_1 at Q5
EACH RING: $6 \times 1.5T$; 8cm




Fig. IV.2-1. Layout of the Collider.

Note: No interference with beam dump

DAY-ONE: 1 Power supply EACH RING