

BNL-108531-2015-TECH C-A/AP/548;BNL-108531-2015-IR

Gold ion parameters for the 2015 PP-on-Au setup in RHIC

C. J. Gardner

August 2015

Collider Accelerator Department Brookhaven National Laboratory

U.S. Department of Energy

USDOE Office of Science (SC), Nuclear Physics (NP) (SC-26)

Notice: This technical note has been authored by employees of Brookhaven Science Associates, LLC under Contract No.DE-SC0012704 with the U.S. Department of Energy. The publisher by accepting the technical note for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, worldwide license to publish or reproduce the published form of this technical note, or allow others to do so, for United States Government purposes.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

C-A/AP/548 August 2015

Gold ion parameters for the 2015 PP-on-Au setup in RHIC

C. J. Gardner



Collider-Accelerator Department Brookhaven National Laboratory Upton, NY 11973

U.S. Department of Energy Office of Science, Office of Nuclear Physics

Notice: This document has been authorized by employees of Brookhaven Science Associates, LLC under Contract No. DE-SC0012704 with the U.S. Department of Energy. The United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this document, or allow others to do so, for United States Government purposes.

Gold Ion Parameters for the 2015 PP-on-Au Setup in RHIC

C.J. Gardner

August 25, 2015

In this note the nominal parameters for gold ions in Booster, AGS, and RHIC are given for the 2015 PP-on-Au setup in RHIC.

The setup parameters are summarized in Sections 17, 18, 19.

1 Mass

A gold ion with charge eQ has N = 118 neutrons, Z = 79 protons, and (Z - Q) electrons. Here Q is an integer and e is the positive elementary charge. The mass number is

$$A = N + Z = 197.$$
 (1)

This is also called the number of nucleons. The mass energy equivalent of the ion is

$$mc^2 = am_u c^2 - Qm_e c^2 + E_Q \tag{2}$$

where [1, 2]

$$a = 196.9665687(6) \tag{3}$$

is the relative atomic mass of the neutral gold atom,

$$m_u c^2 = 931.494061(21) \text{ MeV}$$
 (4)

is the mass energy equivalent of the atomic mass constant, and

$$m_e c^2 = 0.510998928(11) \text{ MeV}$$
 (5)

is the electron mass energy equivalent. The binding energy E_Q is the energy required to remove Q electrons from the neutral gold atom. This amounts to [3, 4] 0.3324 MeV for the helium-like gold ion (Q = 77) and 0.5170 MeV for the fully stripped ion. For Q = 32 we have $E_Q = 14.5$ KeV.

Thus the mass energy equivalents for the Au32+, Au77+, and Au79+ ions are

$$mc^{2}(\text{Au}32+) = 183.456851494 \text{ GeV}$$
 (6)

$$mc^{2}(\text{Au77+}) = 183.434174442 \text{ GeV}$$
 (7)

and

$$mc^{2}(\text{Au79+}) = 183.433337044 \text{ GeV}.$$
 (8)

2 Kinetic Parameters

In a circular accelerator the ion moves along an orbit of circumference C with revolution frequency f. The radius of the orbit is defined to be $R = C/(2\pi)$. The velocity of the ion is then

$$v = 2\pi R f. \tag{9}$$

This gives momentum, energy, and kinetic energy

$$p = mc\beta\gamma, \quad E = mc^2\gamma, \quad W = mc^2(\gamma - 1)$$
 (10)

where

$$\beta = v/c, \quad \gamma = 1/\sqrt{1 - \beta^2}.$$
(11)

The magnetic rigidity of the ion in units of Tm is

$$B\rho = kcp/Q \tag{12}$$

where $k = 10^9/299792458$ and cp is given in units of GeV. The angular frequency is

$$\omega = 2\pi f. \tag{13}$$

We also define the phase-slip factor

$$\eta = \frac{1}{\gamma_t^2} - \frac{1}{\gamma^2} \tag{14}$$

where γ_t is the transition gamma. Note that as defined here, η is negative below transition and positive above transition.

3 RF Parameters

1. The stationary bucket area is

$$A_S = 8 \frac{R_s}{hc} \left\{ \frac{2eQV_g E_s}{\pi h |\eta_s|} \right\}^{1/2} \tag{15}$$

where h is the RF harmonic number, V_g is the total RF gap voltage per turn, and the subscript "s" denotes parameter values for the synchronous particle.

2. The half-height of a bucket is

$$\Delta E = \left(\frac{h\omega_s}{8\sqrt{2}}\right) A_S \left| (\pi - 2\phi_s) \sin \phi_s - 2\cos \phi_s \right|^{1/2} \tag{16}$$

where ϕ_s is the synchronous phase.

3. The synchronous phase is given by

$$V_g \sin \phi_s = 2\pi R_s \rho_s \dot{B}/c \tag{17}$$

where ρ_s is the radius of curvature, B is the magnetic field and $\dot{B} = dB/dt$. Employing Gaussian units (R_s and ρ_s in cm, $c = 2.99792458 \times 10^{10}$ cm/s, and \dot{B} in G/s) gives $V_g \sin \phi_s$ in Statvolts. Multiplying by 299.792458 then gives $V_g \sin \phi_s$ in Volts.

4. The width of a bucket is

$$\Delta t = \frac{|\pi - \phi_s - \phi_e|}{h\omega_s} \tag{18}$$

where the phase ϕ_e satisfies

$$\cos(\pi - \phi_s) - \cos\phi_e = -(\pi - \phi_s - \phi_e)\sin\phi_s.$$
 (19)

5. The area of a bucket is

$$A_{\rm bk} = \alpha(\phi_s) A_S \tag{20}$$

where

$$\alpha(\phi_s) = \frac{\sqrt{2}}{8} \int_{\phi_L}^{\phi_R} |(\pi - \phi_s - \phi) \sin \phi_s - \cos \phi_s - \cos \phi|^{1/2} \, d\phi. \quad (21)$$

Below transition we have $\phi_e < \pi - \phi_s$ and the limits of integration are $\phi_L = \phi_e$ and $\phi_R = \pi - \phi_s$. Above transition we have $\pi - \phi_s < \phi_e$ and the limits of integration are $\phi_L = \pi - \phi_s$ and $\phi_R = \phi_e$. The integral $\alpha(\phi_s)$ must be evaluated numerically. An approximate expression is [5]

$$\alpha(\phi_s) \approx \frac{1 - \sin \phi_s}{1 + \sin \phi_s}.$$
(22)

6. The synchrotron frequency for small-amplitude oscillations about ϕ_s is

$$F_s = \frac{c}{2\pi R_s} \left\{ \frac{-h\eta_s e Q V_g \cos \phi_s}{2\pi E_s} \right\}^{1/2}$$
(23)

and the corresponding synchrotron tune is $Q_s = 2\pi F_s/\omega_s$. Note that measurement of F_s gives a value for $V_g \cos \phi_s$, while measurement of dB/dt gives a value for $V_g \sin \phi_s$. These two can be used to obtain V_g and ϕ_s .

7. Let ϕ_l and ϕ_r be the phases at the left and right boundries of a bunch matched to a bucket. We have

$$\phi_l < \phi_s < \phi_r \tag{24}$$

and the width of the bunch is

$$\Delta t = \frac{\Delta \phi}{h\omega_s}, \quad \Delta \phi = \phi_r - \phi_l. \tag{25}$$

In terms of $\Delta \phi$ and ϕ_s we have

$$\phi_r = \frac{\Delta\phi}{2} + \arcsin\left\{\frac{\Delta\phi\sin\phi_s}{2\sin(\Delta\phi/2)}\right\}$$
(26)

and

$$\phi_l = -\frac{\Delta\phi}{2} + \arcsin\left\{\frac{\Delta\phi\sin\phi_s}{2\sin(\Delta\phi/2)}\right\}.$$
(27)

If $\Delta \phi$ is small we have

$$\sin(\Delta\phi/2) \approx \frac{\Delta\phi}{2}, \quad \frac{\Delta\phi\sin\phi_s}{2\sin(\Delta\phi/2)} \approx \sin\phi_s$$
 (28)

and

$$\phi_l \approx \phi_s - \frac{\Delta \phi}{2}, \quad \phi_r \approx \phi_s + \frac{\Delta \phi}{2}.$$
 (29)

8. The half-height of a bunch matched to a bucket is

$$\Delta E = \left(\frac{h\omega_s}{8\sqrt{2}}\right) A_S \left|\cos\phi_r - \cos\phi_s + (\phi_r - \phi_s)\sin\phi_s\right|^{1/2}.$$
 (30)

9. The area of a bunch matched to a bucket is

$$A_{\rm b} = F(\phi_s, \Delta\phi) A_S \tag{31}$$

where

$$F(\phi_s, \Delta \phi) = \frac{\sqrt{2}}{8} \int_{\phi_l}^{\phi_r} |\cos \phi_l - \cos \phi + (\phi_l - \phi) \sin \phi_s|^{1/2} \, d\phi.$$
(32)

The integral $F(\phi_s, \Delta \phi)$ must be evaluated numerically. If $\Delta \phi$ is small we have

$$F(\phi_s, \Delta \phi) \approx \frac{\pi}{64} (\Delta \phi)^2 \left| \cos \phi_s \right|^{1/2}.$$
(33)

4 Ring Parameters

Parameter	Booster	AGS	RHIC	Unit
C_I	C_b	C_a	$C_r + \delta C$	m
C_E	$C_a/4$	$4(C_r + \delta C)/19$	$C_r + \delta C$	m
ρ	13.8656	85.378351	242.7806	m
$\gamma_{ m tr}$	4.832	8.5	22.89	

Here C_I and C_E are the circumferences of the closed orbits in the machines at injection and extraction (or store) respectively. C_b , C_a , and C_r are the circumferences of the "design" orbits in Booster, AGS, and RHIC respectively. These are

$$C_b = 201.780, \quad C_a = 2\pi (128.4526), \quad C_r = 3833.845181$$
(34)

meters. δC is the shift (if any) of the RHIC orbit circumference from the design value C_r . Note that $4(C_r/19) = 2\pi(128.4580)$ m which gives an AGS radius at extraction approximately 5 mm larger than the "design" AGS radius (128.4526 m) reported by Bleser [6, 7]. The radius of curvature ρ in the Booster and AGS main dipoles is given in Refs. [6, 7, 8]. The RHIC ring parameters are taken from Ref. [9] and from MAD runs by Steve Tepikian.

5 Initial Conditions and Assumptions

- 1. The revolution frequency of the Au32+ ion (from EBIS) at Booster injection is 96.640 kHz. The radius is taken to be the nominal radius $C_b/(2\pi)$.
- 2. The revolution frequency of the Au32+ ion at Booster extraction is f = 658.91 KHz [10]. The radius is taken to be one fourth the nominal AGS radius $C_a/(2\pi)$. The corresponding magnetic rigidity is $B\rho = 9.4620277$ Tm. The rigidity that can be extracted from Booster into the BTA line is limited by the F3 extraction kicker. The advertised limit is $B\rho = 9.5$ Tm [11].
- 3. The set revolution frequency of the Au77+ ion at AGS injection is f = 163.125 KHz. This gives an energy loss of 2.453 MeV per nucleon in the BTA stripper.
- 4. The magnetic rigidity of the Au79+ ion at RHIC injection is taken to be $B\rho = 81.11378003$ Tm.
- 5. The circumference shift in RHIC yellow ring at Au79+ injection is $\delta C = -3.7203 \text{ mm} [12].$
- 6. The circumference shift in RHIC yellow ring at PP injection is $\delta C = -6.24572 \text{ mm} [12].$
- 7. The circumference shift in RHIC yellow ring at Store is $\delta C = -6.14315 \text{ mm} [12].$
- 8. The magnetic rigidity of the Au79+ ion in RHIC at PP injection is $B\rho = 195.647211941$ Tm [12].
- 9. The magnetic rigidity of the Au79+ ion at RHIC store is $B\rho = 812.990761749$ Tm [12].

The parameter values given in the following sections are calculated with these initial conditions and assumptions. For many of the parameters more digits are given than would be warranted by the precision with which the parameter could be measured; this is done for computational convenience.

6 Bunch Merging

The desired number of ions per bunch in RHIC is achieved by merging bunches in both Booster and AGS as described in [13, 14]. Each of the merges is a 2 to 1 merge in which 2 adjacent bunches are merged into 1. If the merge is done sufficiently slowly, the gross emittance of the merged bunch will be the sum of the emittances of the initial 2 bunches. In this case we say that the gross emittance has been conserved. If the merge is done too quickly, the merged bunch will be diluted with empty phase space, making its gross emittance larger than that of the slowly merged bunch. In this case we say that there has been emittance growth (even though the area of phase space occupied by beam has not changed). Careful measurements [15] by K.L. Zeno have shown that the growth in longitudinal emittance during the merges is relatively small.

7 Longitudinal Emittance

The longitudinal emittance per nucleon of unbunched beam in Booster at injection is

$$\mathcal{E} = \frac{2}{A} \Delta E \Delta T \tag{35}$$

where ΔE is the energy half-width of the beam,

$$\Delta T = \frac{1}{f} = \frac{2\pi R}{c\beta} \tag{36}$$

is the revolution period, and A is the number of nucleons. Using the differential relation

$$\Delta E = \beta^2 \frac{\Delta p}{p} mc^2 \gamma \tag{37}$$

we have

$$\mathcal{E} = \frac{2\beta^2 \gamma}{f} \frac{mc^2}{A} \frac{\Delta p}{p} \tag{38}$$

where Δp is the momentum half-width of the unbunched beam. Taking

$$f = 96.640 \text{ kHz}$$
 (39)

gives

$$\Delta T = 10.3476821192 \,\mu \text{s} \tag{40}$$

$$\beta = 0.0650450626079, \quad \gamma = 1.00212216641 \tag{41}$$

and

$$\frac{2\beta^2\gamma}{f} = 87.7450074295 \text{ ns.}$$
 (42)

For Au32+ ions we have

$$\frac{mc^2}{A} = 0.931253053269 \text{ GeV}$$
(43)

which gives

$$\frac{2\beta^2\gamma}{f}\frac{mc^2}{A} = 81.7128060778 \text{ eV s.}$$
(44)

For a fractional momentum half-width of

$$\frac{\Delta p}{p} = 0.001,\tag{45}$$

equation (38) then gives longitudinal emittance (per nucleon)

$$\mathcal{E} = 0.0817128060778 \text{ eV s.}$$
(46)

For the merging scheme described in [13, 14], four Booster loads end up in one AGS bunch. The minimum longitudinal emittance of that bunch would then be

$$4\mathcal{E} = 0.32685 \text{ eV s.} \tag{47}$$

This is to be compared with the measured value of 0.428 eVs obtained by Zeno [15].

Measurements [15, 16] show that the longitudinal emittance of unbunched Au32+ beam in Booster at injection can be made as small as

$$\mathcal{E} = 0.032 \text{ eV s.} \tag{48}$$

Unfortunately, this only can be done by increasing the RF capture time well beyond the 8 ms allowed for the nominal magnetic cycle. The corresponding fractional momentum half-width is

$$\frac{\Delta p}{p} = 0.0003916.$$
 (49)

A detailed account of the longitudinal emittance evolution in Booster and AGS is given in [15] and [13].

8 Minimum RF Voltage Required to Capture the Unbunched Beam

In order to capture the unbunched beam into h buckets we must have RF voltage V_g (i.e. total gap voltage per turn) such that

$$\mathcal{E} \le \frac{hA_S}{A} \tag{50}$$

where A_S is given by (15). Thus we must have

$$\frac{2\beta^2\gamma}{f}\frac{mc^2}{A}\frac{\Delta p}{p} \le \frac{8R}{cA}\left\{\frac{2eQV_gE}{\pi h|\eta|}\right\}^{1/2}$$
(51)

which gives

$$2\beta^2 \gamma \left(\frac{2\pi R}{c\beta}\right) \frac{mc^2}{A} \frac{\Delta p}{p} \le \frac{8R}{c} \left(\frac{2\gamma}{\pi h|\eta|}\right)^{1/2} \frac{mc^2}{A} \left(\frac{eQV_g}{mc^2}\right)^{1/2} \tag{52}$$

$$\beta^2 \gamma \left(\frac{\pi}{\beta}\right) \frac{\Delta p}{p} \le 2 \left(\frac{2\gamma}{\pi h |\eta|}\right)^{1/2} \left(\frac{e Q V_g}{m c^2}\right)^{1/2} \tag{53}$$

$$\beta^2 \gamma^2 \pi^2 \left(\frac{\Delta p}{p}\right)^2 \le \left(\frac{8\gamma}{\pi h|\eta|}\right) \left(\frac{Q}{mc^2}\right) eV_g \tag{54}$$

and

$$\frac{1}{8} h \pi^3 \beta^2 \gamma \left| \eta \right| \left(\frac{mc^2}{Q} \right) \left(\frac{\Delta p}{p} \right)^2 \le e V_g.$$
(55)

Here

$$h = 4 \tag{56}$$

and taking revolution frequency

$$f = 96.640 \text{ kHz}$$
 (57)

we have

$$\eta = -0.952939329734 \tag{58}$$

 $\quad \text{and} \quad$

$$\frac{1}{8} h \pi^3 \beta^2 \gamma \left| \eta \right| = 0.0626374709945.$$
(59)

For the Au32+ ion we have mass energy equivalent per unit charge

$$\frac{mc^2}{Q} = 5.73302660918 \text{ GeV.}$$
(60)

Taking fractional momentum half-width

$$\frac{\Delta p}{p} = 0.001\tag{61}$$

then gives

$$359.102287944 \text{ volts} \le V_g.$$
 (62)

9 Inflector Voltage

At Booster injection, the voltage V_I required for particles with mass m, velocity $c\beta$, and charge eQ to follow the nominal trajectory through the inflector is given by

$$eV_I = \frac{G}{R_I} \left(\frac{mc^2}{Q}\right) \beta^2 \gamma.$$
(63)

Here G = 0.021 m is the gap between the cathode and septum of the inflector and $R_I = 8.74123$ m is the radius of curvature along the nominal trajectory. Using the values of β , γ , and mc^2/Q given by (41) and (60), we obtain

$$V_I = 58.396 \text{ kV}$$
 (64)

for Au32+ ions from EBIS. Because of an unresolved calibration problem, the actual setpoint for the inflector voltage needs to be

$$V_I(\text{setpoint}) = 59.740 \text{ kV}.$$
(65)

10 Booster Injection Field

The nominal magnetic field in the Booster dipoles at injection is

$$B = (B\rho)/\rho \tag{66}$$

where $B\rho$ is given by (12) and ρ is the nominal radius of curvature. Writing

$$B\rho = \frac{10^9}{c} \left(\frac{mc^2}{Q}\right) \beta\gamma \tag{67}$$

and using the values of β , γ , and mc^2/Q given by (41) and (60), we obtain

$$B\rho = 1.24651715338 \text{ Tm.}$$
 (68)

Here we have used the mass energy equivalent mc^2 in units of GeV and the velocity of light in units of m/s. Using

$$\rho = 13.8656 \,\mathrm{m}$$
(69)

we then obtain

$$B = 898.999793284 \text{ Gauss}$$
(70)

for Au32+ ions from EBIS.

The magnetic field is measured with a Hall probe and the Booster Gauss Clock. The Hall probe sits in the reference dipole and gives the value of the field at BT0. The Gauss Clock gives the change in field between BT0 and the time of measurement. The measured field is defined to be the field at BT0 plus the field change given by the Gauss Clock. For Au32+ ions from EBIS the measured field at injection is

$$B(\text{measured}) = 894.0 \text{ Gauss.}$$
(71)

11 AGS Injection Field

Similarly, the nominal magnetic field in the AGS dipoles at injection is B = 454.96 Gauss for the Au77+ ions. The measured magnetic field is 482.0 gauss [17].

12 BTA Stripper

The stripper [26, 27] used to strip gold ions in the BTA (Booster-To-AGS) transfer line consists of a 6.45 mg/cm² aluminum foil followed by a 8.39 mg/cm² carbon foil. In Section 21 we use these surface densities to calculate the energy loss of Au77+ ions in the foils.

13 AGS Injection Septum Magnet Current

The field required in the L20 septum magnet is

$$B = (B\rho)/\rho \tag{72}$$

where $B\rho$ is the magnetic rigidity of the beam and $\rho = 18.625$ m [19] is the radius of curvature of the nominal trajectory through the magnet. The required current is given by

$$NI = gB/\mu_0 \tag{73}$$

where N = 1 is the number of conductor turns; g = 0.0467 m [19] is the magnet gap; and $\mu_0 = 4\pi \times 10^{-7}$ Tm/A.

For Au77+ ions at injection, the magnetic rigidity is $B\rho = 3.88434088$ Tm. This gives B = 0.208555 T and I = 7750 A.

For comparison, the magnetic rigidity of polarized protons at AGS injection is $B\rho = 7.205178$ Tm. This gives B = 0.3869 T and I = 14380 A.

14 AGS Injection Kicker Current

The current required in the A5 kicker is [18, 19]

$$I = \frac{B\rho}{K}\sin\phi \tag{74}$$

where

$$K = 1.8718 \times 10^{-5} \,\mathrm{Tm/A} \tag{75}$$

and

$$\phi = 3.35 \text{ milliradians} \tag{76}$$

is the desired kick angle. Using the calculated values of $B\rho$ at AGS injection we obtain a current of 695.2 A for Au77+ ions. The maximum available current is 1100 A.



15 AGS Injection Kicker <u>Short</u> Pulse Waveforms

Figure 1: AGS injection kicker waveforms in the short pulse mode. The three traces are from the three modules of the kicker. They were taken by Yugang Tan on 9 Dec 2011. The time per division is 200 ns. The RF bucket width on the AGS injection porch is 383 ns for Au77+ ions. In order to put beam into adjacent buckets, the rise time of the kicker must be less than or equal to T - W, where T is the bucket width and W the bunch width. The rise time is approximately 100 ns, which implies that the bunch width must be less than or equal to 283 for Au77+ bunches. A single bunch of this width easily fits on the flattop portion of the pulse which is some 600 ns long. The total width of the pulse is approximately 1000 ns. With this kicker pulse one could in principle fill 14 of the 16 RF buckets on the AGS injection porch. The pulse is too wide to fill the remaining buckets without interfering with beam in the adjacent buckets. This is not an issue as only 8 of the buckets need to be filled. One workable filling pattern is four adjacent filled buckets followed by four adjacent empty buckets, followed by another four adjacent filled buckets. Another workable pattern is eight adjacent filled buckets followed eight empty buckets.

16 AGS Injection Kicker Long Pulse Waveforms



Figure 2: AGS injection kicker waveforms in the long pulse mode. The three traces are from the three modules of the kicker. They were taken by Yugang Tan in Oct 2010. The time per division is 200 ns. The RF bucket width on the AGS injection porch is 383 ns for Au77+ ions. Here the flattop portion of the pulse is some 1300 ns long. The total pulse width is approximately 2000 ns. In principle this kicker pulse could be used to fill 8 buckets with a filling pattern of four adjacent filled buckets followed by four adjacent empty buckets, followed by another four adjacent filled buckets.

Parameter	Injection	Merge porch	Extraction	Unit
Q	32	32	32	
mc^2	183.456851	183.456851	183.456851	${\rm GeV}$
W/A	1.9762739452	49.259795	107.75879	MeV
cp/A	60.701960016	306.87652	460.77475	MeV
E/A	0.9332293272	0.98051285	1.0390118	${\rm GeV}$
$B\rho$	1.24651715338	6.3017214	9.4620277	Tm
β	0.065045062608	0.31297552	0.44347401	
$\gamma - 1$	0.002122166406	0.052896251	0.11571376	
η	-0.953	-0.859	-0.7605	
$\epsilon_H (95\%)$	12.1π	12.1π	12.1π	mm mrad
$\epsilon_V (95\%)$	5.68π	5.68π	5.68π	mm mrad
h	4	1	1	
hf	386.560	465.000	658.910	KHz
R	$201.780/(2\pi)$	$201.780/(2\pi)$	128.4526/4	m

17 Gold in Booster

Here ϵ_H and ϵ_V are the normalized horizontal and vertical transverse emittances. These follow from the assumption that during injection the horizontal and vertical acceptances in Booster are completely filled. The horizontal and vertical acceptances are 185π and 87π mm mrad (un-normalized) respectively.

Parm	Injection	Injection	Ext	Ext	Ext	Unit
V_g	0.403	5.730	25.2	25.2	25.2	kV
A_S	4.263	16.076	318.54	318.54	318.54	eVs
dB/dt	0	0	70	35	0	G/ms
ϕ_s	0	0	50.999	22.866	0	deg
F_s	0.3065	1.1557	0.8139	0.9849	1.0260	kHz
$A_{\rm bk}$	4.263	16.076	36.294	140.88	318.54	eVs
A_b	1.576	3.8907	17.533	17.533	17.533	eVs
Δt	1196	947.0	299.3	263.8	257.7	ns
ΔE	0.8596	2.654	37.98	42.50	43.45	MeV

Parameter	Injection	Injection	Extraction	Unit
No. Bunches	4	4	1	
Bucket Width	2586.92053	2586.92053	1517.65795	ns
Ions/Bunch	1.12/4	1.12/4	1.007	$10^9 [20]$
Bunch Area	0.032/4 [16]	0.0790/4 [21]	0.089[22]	eVs/A

Parameter	Injection	Transition	Extraction	Unit
Q	77	77	77	
mc^2	183.434174	183.434174	183.434174	${\rm GeV}$
W/A	0.10529199	6.98353456	8.86486803967	${\rm GeV}$
cp/A	0.45515837	7.85970883	9.75165192744	GeV
E/A	1.0364299	7.91467250	9.79600598100	GeV
$B\rho$	3.88434088	67.0750887	83.2210113659	Tm
β	0.43915981	0.993055472	0.995472230862	
γ	1.1130788	8.5000	10.5204669965	
η	-0.793	0.0	0.00481	
$\epsilon_H (95\%)$	$\leq 12\pi$	$\leq 12\pi$	$\leq 12\pi$	mm mrad
$\epsilon_V (95\%)$	$\leq 12\pi$	$\leq 12\pi$	$\leq 12\pi$	mm mrad
h	16	12	12	
hf	2.610000	4.42642072	4.43701154342	MHz
R	128.4526	128.4526	128.457856737	m

18 Gold in AGS

Parameter	Injection	Injection	Extraction	Unit
h	16	4	12	
V_g	17.267	6.567	192.0	kV
A_S	24.998	123.33	5070	eVs
dB/dt	0	0	0	G/ms
ϕ_s	0	0	180	degrees
F_s	1.347	0.4154	0.0985	kHz
$A_{ m bk}$	24.998	123.33	5070	eVs
A_b	19.7	84.316	137.9	eVs
Δt	287.0	1034 [23]	26.8	ns
ΔE	47.31	55.13	3281	MeV

Parameter	Injection	Injection	Extraction	Unit
h	16	4	12	
Bucket Width	383.142	1532.567	225.377	ns
No. of Bunches	8	2	2	
Ions/Bunch	0.55725	2.229	2.055	$10^9 [20]$
Bunch Area	0.10 [13]	0.428 [13]	0.70 [24]	eVs/A

Parameter	Injection	PP Injection	Store	Unit
Q	79	79	79	
mc^2	183.433337	183.433337	183.433337	${ m GeV}$
W/A	8.86482757134	22.6082598553	96.8121411674	${ m GeV}$
cp/A	9.75160741084	23.5209701874	97.7388396187	GeV
E/A	9.79596126192	23.5393935459	97.7432748580	GeV
$B\rho$	81.11378003	195.647211941	812.990761749	Tm
β	0.995472230863	0.999217339291	0.999954623586	
γ	10.5204669974	25.2803585393	104.972331951	
η	-0.00713	0.0003439	0.001818	
$\epsilon_H (95\%)$	$\leq 10\pi$	$\leq 10\pi$	$\leq 10\pi$	mm mrad
$\epsilon_V (95\%)$	$\leq 10\pi$	$\leq 10\pi$	$\leq 10\pi$	mm mrad
f	77.8423077794	78.1352131060	78.1928640023	kHz
h	360	360	360	
hf	28.0232308006	28.1286767182	28.1494310408	MHz
δC	-3.7203	-6.24572	-6.14315	mm

19 Gold in RHIC

Parameter	Injection	Store	Unit
h	360	2520	
V_g	393.1	3000	kV
A_S	174.4	162.7	eVs
dB/dt	0	0	G/ms
ϕ_s	0	180	degrees
F_s	0.200	0.234	m kHz
$A_{\rm bk}$	174.4	162.7	eVs
A_b	137.9	137.9	eVs
A_b	0.70	0.70	eVs/A [25]
Δt	26.8	4.03	ns
ΔE	3549	23900	MeV

20 Center-of-Mass Energy for Proton-Ion Collisions in RHIC

Let E_1 and P_1 be the energy and momentum of an ion circulating in RHIC, and let E_2 and $-P_2$ be the energy and momentum of the counter-circulating ion. The counter-circulating ion may be identical to the circulating one or it may be some other kind of ion.

The center-of-mass (CM) mass-energy equivalent, Mc^2 , is given by the Lorentz invariant

$$M^{2}c^{4} = (E_{1} + E_{2})^{2} - (cP_{1} - cP_{2})^{2}$$
(77)

where

$$E_1 = m_1 c^2 \gamma_1, \quad cP_1 = m_1 c^2 \beta_1 \gamma_1$$
 (78)

and

$$E_2 = m_2 c^2 \gamma_2, \quad cP_2 = m_2 c^2 \beta_2 \gamma_2.$$
 (79)

Thus we have

$$M^{2} = (m_{1}\gamma_{1} + m_{2}\gamma_{2})^{2} - (m_{1}\beta_{1}\gamma_{1} - m_{2}\beta_{2}\gamma_{2})^{2}$$
(80)

$$M^{2} = m_{1}^{2} \left(\gamma_{1}^{2} - \beta_{1}^{2} \gamma_{1}^{2} \right) + m_{2}^{2} \left(\gamma_{2}^{2} - \beta_{2}^{2} \gamma_{2}^{2} \right) + 2m_{1} m_{2} \gamma_{1} \gamma_{2} \left(1 + \beta_{1} \beta_{2} \right)$$
(81)

and

$$M^{2} = m_{1}^{2} + m_{2}^{2} + 2m_{1}m_{2}\gamma_{1}\gamma_{2}\left(1 + \beta_{1}\beta_{2}\right).$$
(82)

Here we have used the identities

$$\gamma_1^2 - \beta_1^2 \gamma_1^2 = 1, \quad \gamma_2^2 - \beta_2^2 \gamma_2^2 = 1.$$
 (83)

For Proton-Ion collisions we take

$$\beta_1 = \beta_p, \quad \gamma_1 = \gamma_p \tag{84}$$

$$\beta_2 = \beta_I, \quad \gamma_2 = \gamma_I \tag{85}$$

and

$$m_1 = m_p, \quad m_2 = m_I / A \tag{86}$$

where A is the atomic number (number of nucleons) of the ion, and the subscripts p and I refer to the proton and ion respectively. Thus (82) becomes

$$M^{2} = m_{p}^{2} + \left(\frac{m_{I}}{A}\right)^{2} + 2m_{p}\left(\frac{m_{I}}{A}\right)\gamma_{p}\gamma_{I}\left(1 + \beta_{p}\beta_{I}\right)$$
(87)

where

$$\beta_p \gamma_p = \left\{ \gamma_p^2 - 1 \right\}^{1/2}, \quad \beta_I \gamma_I = \left\{ \gamma_I^2 - 1 \right\}^{1/2}.$$
 (88)

The mass-energy equivalent of the proton is [2]

$$m_p c^2 = 0.938272046(21) \text{ GeV}.$$
 (89)

For the <u>Au79+ ion</u>, the atomic number is

$$A = 197 \tag{90}$$

and the mass-energy equivalent is

$$m_I c^2 = 183.433337044 \text{ GeV}.$$
 (91)

For polarized protons, the desired values of γ_p are quantized by the relation

$$G\gamma_p = k + \frac{1}{2} \tag{92}$$

where k is a non-negative integer and

$$G = (g_p - 2)/2. (93)$$

Here the proton g factor is [2]

$$g_p = 5.585694713(46) \tag{94}$$

which gives

$$G = 1.79284735650. \tag{95}$$

For polarized protons with

$$k = 198 \tag{96}$$

and Au79+ ions with

$$\gamma_I = 104.997926997 \tag{97}$$

we then have CM mass-energy equivalent

$$Mc^2 = 201.533112539 \text{ GeV.}$$
 (98)

21 Au77+ Energy Loss in the BTA Stripper Foils

The stripper used to strip gold ions consists of a 6.45 mg/cm^2 aluminum foil followed by a 8.39 mg/cm^2 "glassy" carbon foil [26, 27]. We can estimate the energy loss in the foils as follows:

The kinetic energy of a proton that has the same velocity as the Au77+ ion just upstream of the aluminum foil is

$$W_p = 108.6 \text{ MeV.}$$
 (99)

The rate of energy loss of a proton passing through the foil with kinetic energy W_p is [28]

$$-\frac{dE_p}{dx} = 5.348 \text{ MeV cm}^2/\text{g.}$$
(100)

The rate of energy loss of the Au77+ ion is obtained by scaling the Bethe-Bloch result for protons [29]. Thus

$$-\frac{dE}{dx} = -Z^2 \frac{dE_p}{dx} \,\mathrm{cm}^2/\mathrm{g} \tag{101}$$

where Z = 77. Multiplying this by the surface density of the aluminum foil (6.45 mg/cm²) gives

$$\Delta E_a = 1.038 \text{ MeV per nucleon.}$$
(102)

This is the energy lost by the Au77+ ion upon passing through the aluminium foil. The kinetic energy of a proton that has the same velocity as the Au77+ ion just downstream of the aluminum foil is then

$$W_p = 107.5 \text{ MeV.}$$
 (103)

The rate of energy loss of a proton passing through the carbon foil with this kinetic energy is [28]

$$-\frac{dE_p}{dx} = 6.180 \text{ MeV cm}^2/\text{g.}$$
(104)

Using this result in (101) with Z = 77, and multiplying by the surface density of the carbon foil (8.39 mg/cm²) gives

$$\Delta E_c = 1.561 \text{ MeV per nucleon.}$$
(105)

The total energy lost upon passing through both foils is then

$$\Delta E = \Delta E_a + \Delta E_c = 2.599 \text{ MeV per nucleon.}$$
(106)

This agrees reasonably well with the value 2.453 MeV per nucleon obtained in Section 5.

References

- J.S. Coursey, D.J. Schwab, and R.A. Dragoset, "Atomic Weights and Isotopic Compositions", Nuclear Physics Data, Physical Reference Data, www.nist.gov.
- [2] P.J. Mohr and B.N. Taylor, "Values of Fundamental Physical Constants", Physical Constants, Physical Reference Data, www.nist.gov.
- [3] K.A. Brown, C. Gardner and P. Thieberger, "Rest Mass of Fully Stripped Ions in RHIC: Updated Values", C-A/AP/Note 293, October 2007.
- [4] G.C. Rodrigues, P. Indelicato, J.P. Santos, P. Patte, and F. Parente, "Systematic Calculation of Total Atomic Energies of Ground State Configurations", Atomic Data and Nuclear Data Tables 86 (2004) 117–233.
- [5] S.Y. Lee, "Accelerator Physics", World Scientific, 1999, pp. 229–230
- [6] E.J. Bleser, "Where are the AGS Magnets", Accelerator Division Technical Note 215, May 20, 1985.
- [7] C.J. Gardner, "Notes on Orbit Equations in the AGS", C-A/AP/Note 164, September 2004.
- [8] R. Thern, "Booster Dipole Production Measurements", Booster Technical Note 190, March 13, 1991.
- [9] W. Fischer and S. Peggs, "RHIC Parameters", Revision of 3/18/97.
- [10] K.L. Zeno, Booster-AGS-EBIS-2012 elog, 16 May 2012, entry 15:50.
- [11] W. Zhang, R. Sanders, A. Soukas and J. Tuozzolo, "An Overview of the Fast Injection-Extraction Kicker Systems of the Brookhaven AGS-Booster Complex", PAC99, pp. 1264–1266.
- [12] As calculated by Al Marusic. The circumference shifts are due to the unequal rigidities of polarized protons (PP) and Au79+ ions in the DX magnets.
- [13] C.J. Gardner, et al, "Operation of the RHIC Injector Chain with Ions from EBIS", Proceedings of IPAC2015

- [14] C.J. Gardner, "Simulations of Merging and Squeezing Bunches in Booster and AGS", C-A/AP/Note 460, July 2012.
- [15] K.L. Zeno, "Longitudinal Emittance Measurements in the Booster and AGS during the 2014 RHIC Gold Run", C-A/AP/Note 523, August 2014.
- [16] K.L. Zeno, Booster-AGS-EBIS-2014 elog, 3 July 2014, entries 13:29 and 13:33.
- [17] K.L. Zeno, Booster-AGS-EBIS-2014 elog, 21 February 2014, entry 19:23.
- [18] C.J. Gardner, "Determination of the AGS Injection Kicker Strength from Beam Measurements", C-A/AP/Note 91, December 2002.
- [19] C.J. Gardner, "AGS Injection with an Additional Kicker in the A10 Straight Section", C-A/AP/Note 217, September 2005.
- [20] K.L. Zeno, Booster-AGS-EBIS-2014 elog, 29 May 2014, entry 18:18.
- [21] K.L. Zeno, Booster-AGS-EBIS-2014 elog, 26 June 2014, entries 12:42 and 13:59.
- [22] K.L. Zeno, Booster-AGS-EBIS-2014 elog, 4 June 2014, entry 17:48 and 24 June 2014, entry 17:27.
- [23] K.L. Zeno, Booster-AGS-EBIS-2014 elog, 3 February 2014, entry 17:40.
- [24] K.L. Zeno, Booster-AGS-EBIS-2014 elog, 21 March 2014, entry 18:13;
 23 April 2014, entries 21:04; 2 May 2014, entries 17:40 and 17:57.
- [25] Here we take the longitudinal emittance to be the same as that at AGS extraction. This gives a lower bound on the longitudinal emittance in RHIC.
- [26] C.J. Gardner, et al, "Setup and Performance of the RHIC Injector Accelerators for the 2007 Run with Gold Ions", Proceedings of PAC07, pp. 1862–1864.
- [27] P. Thieberger, et al, "Improved Gold Ion Stripping at 0.1 and 10 GeV/nucleon for the Relativistic Heavy Ion Collider", Phys. Rev. ST Accelerators and Beams 11, 011001 (2008).

- [28] M.J. Berger, J.S. Coursey, M.A. Zucker and J. Chang, "Stopping-Power and Range Tables for Electrons, Protons, and Helium Ions", www.nist.gov/physlab/data/star/index.cfm
- [29] W.R. Leo, "Techniques for Nuclear and Particle Physics Experiments", Second Revised Edition, Springer-Verlag, 1994, pp. 24–28.